



US010125908B2

(12) **United States Patent**
Kujawski, Jr.

(10) **Patent No.:** **US 10,125,908 B2**
(45) **Date of Patent:** **Nov. 13, 2018**

(54) **QUICK CONNECT FLUID COUPLING WITH INTEGRATED CHECK VALVE**

(71) Applicant: **Oetiker NY, Inc.**, Lancaster, NY (US)

(72) Inventor: **James Kujawski, Jr.**, Attica, NY (US)

(73) Assignee: **Oetiker NY, Inc.**, Lancaster, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 80 days.

(21) Appl. No.: **15/005,685**

(22) Filed: **Jan. 25, 2016**

(65) **Prior Publication Data**

US 2016/0238173 A1 Aug. 18, 2016

Related U.S. Application Data

(60) Provisional application No. 62/117,635, filed on Feb. 18, 2015.

(51) **Int. Cl.**
F16L 37/088 (2006.01)
F16L 37/413 (2006.01)

(52) **U.S. Cl.**
CPC **F16L 37/413** (2013.01); **F16L 37/088** (2013.01); **Y10T 137/7929** (2015.04)

(58) **Field of Classification Search**
CPC .. F16L 37/088; F16L 37/413; Y10T 137/7929
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

857,897 A 6/1907 Patterson
2,377,812 A 6/1945 Scheiwer

2,868,563 A * 1/1959 Wood F16L 37/086
137/614.04
3,052,261 A * 9/1962 Nyberg A62C 33/00
137/614.04
3,199,831 A * 8/1965 Sully A01G 25/16
141/349
3,245,423 A 4/1966 Hansen et al.
3,474,810 A 10/1969 Welsh
3,532,101 A 10/1970 Snyder, Jr.
4,391,459 A * 7/1983 Wicke F16B 7/0413
285/238
4,436,125 A 3/1984 Blenkush
5,290,009 A * 3/1994 Heilmann F16L 37/22
251/149.6
5,445,358 A * 8/1995 Anderson F16L 37/38
251/149.6
5,452,924 A 9/1995 Kujawski
5,547,166 A * 8/1996 Engdahl F16L 37/0848
251/149.6
5,607,139 A * 3/1997 Kjellberg F16L 37/42
251/149.1

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1557599 7/2005

Primary Examiner — Craig Schneider


Assistant Examiner — Frederick D Soski

(74) *Attorney, Agent, or Firm* — Simpson & Simpson
PLLC

(57) **ABSTRACT**

A fluid coupling has an outlet for receiving the lead end of a tubular fluid conduit having an external locking shoulder. The coupling also holds within it adjacent an outlet a valve body that is normally closed, but is contacted and displaced against the closing force of a bias spring to open the outlet when the conduit is fully inserted and locked into the coupling by way of said locking shoulder.

19 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,630,570	A *	5/1997	Lacroix	F16L 37/0985 251/149.9	8,191,932	B2 *	6/2012	Davis	F16L 37/23 137/614.05
5,749,606	A	5/1998	Lu et al.		8,267,376	B2	9/2012	Hansen	
5,758,682	A	6/1998	Cain		8,303,000	B2 *	11/2012	Liu	F16L 37/23 137/614.05
5,806,832	A *	9/1998	Larbuissou	F16L 37/42 251/149.6	8,322,941	B2	12/2012	Cermak	
5,816,298	A	10/1998	Stricklin et al.		8,869,828	B2	10/2014	Kamp et al.	
5,909,901	A *	6/1999	Zillig	F16L 37/088 285/308	9,322,500	B2 *	4/2016	Engdahl	F16L 37/0848
6,343,630	B1 *	2/2002	Dubinsky	F16L 37/0848 137/614.05	9,845,908	B2 *	12/2017	Brunella	F16L 37/144
6,719,003	B2 *	4/2004	Schroeder	F16K 15/063 137/234.5	2003/0001384	A1	1/2003	Carroll	
6,890,004	B2 *	5/2005	Naito	F16L 37/22 285/314	2005/0087245	A1	4/2005	Magnus et al.	
7,195,228	B2	3/2007	Tiberghien et al.		2009/0050836	A1 *	2/2009	Chang	F16K 15/021 251/353
7,311,231	B2 *	12/2007	Noell	A45F 3/20 215/388	2010/0224258	A1	9/2010	Steveley et al.	
7,458,392	B2	12/2008	Cornwell		2011/0067225	A1 *	3/2011	Bassaco	F16D 25/08 29/525.01
7,618,070	B2	11/2009	Stoll et al.		2013/0037141	A1	2/2013	Kujawski, Jr. et al.	
					2015/0176738	A1 *	6/2015	Nezu	F16L 37/088 285/321
					2015/0233510	A1 *	8/2015	Nezu	F16L 37/088 285/247
					2017/0074444	A1 *	3/2017	Nezu	F16L 37/14
					2017/0356581	A1 *	12/2017	Trotter	F16L 37/088

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8






FIG. 9




FIG. 10




FIG. 11




FIG. 12

FIG. 13







FIG. 14





1

QUICK CONNECT FLUID COUPLING WITH INTEGRATED CHECK VALVE**CROSS-REFERENCE TO RELATED APPLICATION**

This application is a non-provisional application of U.S. Provisional Application No. 62/117,635, filed Feb. 18, 2015, and claims the benefit thereof.

FIELD OF THE INVENTION

This invention is in the field of fluid couplings and includes a coupling body adapted to lockingly receive therein a tubular conduit that, when fully inserted, opens a check valve to permit through flow.

BACKGROUND

Fluid couplings are commonly used in automotive applications where, for example, coolant or lubricant is pumped from a supply point to a use point and the assembly sequence is such as to require a quick connection somewhere in the flow path.

In application Ser. No. 14/725,639, a coupling with an "assurance cap" is described. The cap provides an indication that the supply tube has been fully inserted into the coupling so as to achieve a secure connection.

BRIEF SUMMARY OF THE INVENTION

The present invention provides a fluid coupling adapted to lockingly and sealingly receive a tubular fluid conduit. The coupling includes a normally closed check valve within the flow path and near an outlet point. The valve length and the location of a lock shoulder on the tubular conduit are such that the lead end of the conduit urges the valve toward an open condition only when the conduit is fully, lockingly inserted into the coupling body. The valve has a fluted body that permits fluid to flow around the valve body and through the coupling outlet. Withdrawal of the conduit, either intentionally or otherwise, causes the valve to close.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a coupling useful in an embodiment of the invention;

FIG. 2 is a cross-sectional view of the coupling of FIG. 1;

FIG. 3 is an end view of the coupling with a check valve installed;

FIG. 4 is an opposite end view of the coupling;

FIG. 5 is a sectional view of the coupling with the check valve in a normally closed position;

FIG. 6 is a perspective view, partly in section, of the coupling with check valve closed;

FIG. 7 is a perspective view of the check valve body;

FIG. 8 is an end view of the check valve body;

FIG. 9 is a side view of the coupling with a tubular conduit partially inserted;

FIG. 10 is a side view in section of the coupling with the conduit partially inserted and the valve closed;

FIG. 11 is a side view of the coupling with the conduit fully inserted and the valve open;

FIG. 12 is a side view in section of the coupling with conduit fully seated and valve open;

FIG. 13 is a perspective view of an alternative design for the check valve body;

2

FIG. 14 is an end view of the alternative valve body;

FIG. 15 is a side view of the alternative valve body; and

FIG. 16 is another perspective view of the check valve showing the recessed end cap.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Referring now to FIGS. 1-12, there is depicted a quick connect fluid coupling 20, including a one-piece metal body 26 with a through bore/flow path adapted to receive one end 22 of a tubular fluid conduit 24 in a locked fluid-sealed state. The coupling body 26 is itself removably mountable in a port of a utilization component (not shown).

The tubular conduit 24 is typically made of metal, but rigid plastic material may also be employed. The tubular conduit 24 has a generally constant diameter extending from the lead end 22. A section 30 extends upstream from the lead end 22 at a first diameter to an outward extending endform 32 having a tapered conical surface 34 which terminates in a large diameter end and a radially extending, back-facing shoulder 36. A fluid path 23 extends through the tubular member 24 for fluid flow.

The coupling body 26 can be, but need not necessarily be, integrally made of a single piece of metallic or plastic material. The coupling body 26 has a through bore 40 extending from a first end 42 to a second end 44. The bore 40 need not have a constant diameter between the first and second ends 42 and 44.

An annular internal groove 46 is formed in the coupling body 26 intermediate the first and second ends 42 and 44. The groove 46 receives a seal member 48, such as an O-ring, for sealing the tubular member 24 to the coupling body 26 to prevent fluid leakage there between.

As described above, the coupling body 26 has an externally threaded end portion 28. The threaded end portion 28 is spaced from the first end 42. A recessed radially inward extending groove 50 can be formed in certain applications adjacent between one end of the threaded end portion 28 and a larger diameter annular collar 52 to receive an external seal member or washer, not shown. A hexagonally shaped portion 54 forming a plurality of hex flats 55 is formed adjacent the annular collar 52. A reduced diameter end portion 56 having a generally constant diameter extends from one end of the hexagonal portion 54 to the second end 44 of the coupling body 26. A recessed, outward opening, annular groove 58 is formed in the receiving portion 56. The groove 58 has a constant closed inner end facing the bore 40 in the coupling body 26 which is interrupted by one or more circumferentially spaced slots 59.

A resilient clip or retainer 60 is mounted in the groove 58. The clip 60 can be, but need not necessarily be, formed of a single piece of spring wire. The clip 60 can be formed with a plurality of inward extending protrusions 62 which project through the slots 59 in the groove 58, when the clip 60 is in a relaxed state behind the shoulder 36 on the tubular member 24 to lock the tubular member 24 to the coupling body 26.

When the first end 22 of the tubular member 24 is inserted into the receiving portion or socket 56 of the coupling body 26, the head portion 32 of the first end 22 of the tubular member 24 slides through the receiving portion 56 toward the first end of the coupling body 26. The inwardly extending protrusions 62 on the clip 60 seated in the groove 58 slide along the radially outward tapered endform 34 on the tubular member 24 causing the resilient clip 60 to expand radially outward moving the protrusions 62 on the clip 60 out of the bore 40 until the shoulder 36 on the endform 32

can slide past the clip 60. At this point, the protrusions 62 on the clip 60 snap radially inward into the bore 40 behind the shoulder 36 locking the tubular member 24 in the coupling body 26.

As shown in FIGS. 10 and 12, the threads 28 on the coupling body 26 threadingly engage internal threads 29 in a bore 27 formed in an external component. This enables fluid to flow between the external component 25 and the tubular member 24, but only when the valve 100 is open as hereinafter described.

Referring briefly to FIG. 2, the bore 40 has a radially inward extending, reduced diameter lip 70 formed at the first end 42. The lip 70 is spaced from a tapered end surface 72 adjacent first end 42 and forms an inward extending shoulder 74 which opens to a first end bore portion 76. The tapered end surface 72 forms a seal seat for a seal member and described hereafter.

A check valve 100 is axially slidably carried in the coupling body 26 in the first end bore portion 76 and is movable between a first closed position blocking or preventing fluid flow through the coupling body 26 and thus fluid flow between the bore 27 in the external component 25 and the bore 23 in the tubular member 24. The valve 100 has a second position shown in FIG. 12 allowing fluid flow between the bore 27 in the external fluid component 25 and the bore 23 in the tubular member 24.

The check valve 100 can be a one-piece body 102 formed of metal or plastic. The body 102 has a first end 104 and an opposed second end 106. A domed head 108 is formed at the first end 26 and has a larger diameter peripheral edge 109 than an adjacent recess 110. The recess 110 receives a seal member, such as an O-ring 112. An adjacent larger diameter wall 114 forms the other end of the recess 110. A fluted plunger 116 is disposed on the body 102 and extends from the wall 114 to the second end 106. The plunger 116 includes four circumferentially spaced, radially extending flutes 120 projecting radially outward from a central stem 122. The flutes 120 may be provided in any number, such as two flutes, three flutes, four flutes, etc.

Interior smoothly curved or angled surfaces 124 are formed at one end of the flutes 120 between the flutes 120 and the wall 114. The surfaces 124 provide a smooth flow directing action on the plunger 116 for fluid flow across the plunger 116, as described hereafter.

Each of the flutes 120 has an enlarged diameter end flange 130 extending radially outward to a larger diameter outer end surface spaced from a radially outer surface 132 on each flute 120. The end flanges 130 form a seat for a biasing member, such as a coil spring 134, hereafter "spring 134", which extends around the outer surface 132 of the flutes 120 between the end flange 130 on the plunger 116 and the shoulder 74 formed by the lip 70 at the first end 42 of the coupling body 26.

Referring to FIGS. 13-16, there is shown an alternative check valve 200 that can replace the plunger 116 of FIGS. 7 and 8. The valve 200 is also one piece of metal or plastic and has a closed, solid, recessed end cap 208 and a base flange 206. The flange 206 performs the function of the shoulder 130 of plunger 116. Adjacent the end cap 208 is a seal groove 210 that receives the O-ring 112 from the embodiment of FIG. 10. Four large flow-through openings 212 are defined by ribs 214 within the valve body 200. Fluid flows through check valve 200 in the same way it flows through the valve 100 shown in FIGS. 7, 8, 12 and 13.

Assembly

In assembling the check valve 100 or 200 in the coupling body 26, the check valve body absent the O-ring 112, is

inserted through the second end 44 of the coupling body 26 until the head 108 or 208 and the edge 109 on the first end 104 of the check valve body projects through the tapered surface 72 and the first end 42 of the coupling body 26, as shown in FIG. 5.

Force is applied to move the check valve body 102 or 200 through the bore portion 76 in the coupling body 26 until the entire recess 110 or 210 on the check valve body 102 or 200 extends outward beyond the first end 42 of the coupling body 26. The O-ring 112 is then installed in the recess 110 or 210 and the force removed to allow the spring 134 to urge the check valve body 102 or 200 toward the second end 44 and retracting the head 102, 204 at the first end 104 of the check valve body 102 toward the first end 42 of the coupling body 26 until the check valve O-ring 112 sealingly engages the tapered surface 72 at the first end 42 of the coupling body 26. The O-ring 112, in this position, not only seals the check valve body 102 in the bore 40 to the coupling body 26, but also retains the check valve 100 or 200 in the coupling body 26.

It will also be understood that in place of the spring 134, a one-time detent mounting arrangement may be provided to mount check valve 100 in the coupling body 26. In this aspect, a radially outward extending may be formed on one end of one or more of the flutes 120 adjacent the wall 114 to engage a detent in the form of an inward extending circumferential recess in the lip 70 adjacent the first end of the coupling body 26. Engagement of the lip in the detent retains the check valve 100 in the closed flow position until the check valve 100 is moved to the open flow position, as described hereafter, when the tubular member 26 is inserted into the bore 40 in the coupling body 26, as shown in FIG. 12.

Operation

In operation, prior to insertion of the tubular member 26 into the bore 40 in the coupling body 26, the spring 134 will urge the check valve 100 or 200 to the first closed position shown in FIG. 5 where the O-ring 112 closes the bore 40 at the first end 42 of the coupling body 26 to fluid flow. When insertion of the tubular member 24 into the coupling body 26 begins, as shown in FIGS. 9 and 10, the first end 22 of the tubular member 24 will engage the end 106 of the flutes 120 on the check valve body 102, as shown in FIG. 10 or the end 206 shown in FIG. 15. In this position, the check valve 100 or 200 remains in the first fluid flow closed position as the O-ring 112 is firmly engage with the tapered surface 72 with the first end 42 of the coupling body 26. Further insertion of the tubular member 24 into the bore 40 in coupling body 26 compresses the spring 134 and urges the check valve body 102 or 200 toward the second open position or toward the right in the orientation shown in FIGS. 9-12. The tubular member 24 continues to be slidably inserted into the coupling body 26 compressing the spring 134 as shown in FIG. 12. The check valve 100 or 200 is now in the second open position for fluid flow between the bore 27 in the external component 25 and the bore 23 in the tubular member 24.

If the tubular member 24 is disengaged from the retainer clip 60 on the coupling body 26, for any reason, whether intentionally or accidentally, the spring 134 will urge the check valve 100 toward the first fluid flow closed position, or to the left in the orientation shown in FIGS. 9-12, until the O-ring 112 again sealingly engages the tapered surface 76 at the first end 42 of the coupling body 26 closing off and blocking further fluid flow between the bore 23 in the tubular member 24 and the bore 27 in the external component 25.

The quick connect fluid connector with integrated check valve **100, 200** provides a number of advantages. The O-ring **112** retains the check valve body within the connector coupling body **26** without the need for additional retention elements. The check valve **100** or **200** is activated and moved between the first and second position only by insertion of the tubular member **24**.

If the coupling body **26** is mounted in the external component **25** or the bore **27** of the external component **25** which functions as an outlet port carrying pressurized fluid, removal or accidental separation of the tubular member **24** from the quick coupling body **26** causes a fluid shutoff, when the tubular member **24** is disconnected from the coupling body **26**. This shutoff feature also allows a customer to ship the external component **25** in a fluid-filled position as the check valve **100** in the quick coupling body **26** will be in the fluid flow closed position prior to insertion of the tubular member **24** into the coupling body **26**.

The quick connector **26** with integrated check valve **100** or **200** can also be used by a customer who manufactures or installs the external component **25** to eliminate the need for insertion of the test plug into the bore **27** in the port of the external component **25**, as well as to eliminate the need for a separate shipping plug when the external component **25** is shipped to an assembly location. This eliminates the need to remove a separate shipping plug prior to tubular member installation and also provides higher sealing capability for a higher pressure leak test.

The quick connector **26** with integrated check valve **100** or **200** is ideal for certain automotive applications, such as turbo engine applications, where the fluid fitting can be used as a shut-off valve when the tubular member **24** is accidentally disconnected from the assembly. This will minimize the potential for thermal events should fluid spray from the disconnected tubular member flow onto adjacent hot turbo application components.

While the invention has been described in connection with certain embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims, which scope is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures as is permitted under the law.

What is claimed is:

1. A quick connect fluid coupling, comprising:
 - a coupling body, including:
 - an inlet;
 - an outlet;
 - a throughbore extending from the outlet to the inlet; and,
 - a circumferential groove arranged proximate the outlet, the circumferential groove comprising one or more slots;
 - a check valve axially displaceably mounted in the inlet, the check valve including:
 - an interior end;
 - an exterior end;
 - a plurality of concave surfaces arranged proximate the exterior end; and,
 - one or more ribs separating the plurality of concave surfaces, each of the one or more ribs comprising:
 - a radially outward facing surface; and,
 - a concave radially inward facing surface;
 - a bias spring operatively disposed between the coupling body and the check valve;

a retainer arranged in the groove, the retainer including at least one protrusion extending through the one or more slots; and,

a tubular conduit having a first end operatively arranged to be inserted in the throughbore, wherein:

- when fully inserted within the coupling body the retainer locks the tubular conduit therein and the check valve is displaced to an open position; and,
- when not fully inserted within the coupling body the tubular conduit is not locked and the check valve is in a closed position.

2. The quick connect fluid coupling as recited in claim 1, wherein the bias spring is retained within the coupling body and operatively arranged to bias the check valve toward the closed position.

3. The quick connect fluid coupling as recited in claim 1, wherein the bias spring is concentrically arranged around the check valve to bias the check valve toward the closed position.

4. The quick connect fluid coupling as recited in claim 1, wherein the bias spring is compressed when the first end engages the interior end to displace the check valve to the open position.

5. The quick connect fluid coupling as recited in claim 1, wherein the tubular conduit further comprises a shoulder operatively arranged proximate the first end to engage the at least one protrusion.

6. The quick connect fluid coupling as recited in claim 1, wherein the check valve comprises a first concave surface, a second concave surface, a third concave surface, and a fourth concave surface, and the first concave surface is separated from the second concave surface by a first rib, the second concave surface is separated from the third concave surface by a second rib, the third concave surface is separated from the fourth concave surface by a third rib, and the fourth concave surface is separated from the first concave surface by a fourth rib.

7. The quick connect fluid coupling as recited in claim 1, wherein each of the one or more ribs comprises a respective end flange.

8. The quick connect fluid coupling as recited in claim 1, wherein each of the one or more ribs extends radially outward from a control stem.

9. The quick connect fluid coupling as recited in claim 1, wherein each of the one or more ribs comprises a width that gradually increases in a radially outward direction.

10. The quick connect fluid coupling as recited in claim 1, wherein an area in a circumferential direction between each of the one or more ribs forms a respective opening.

11. The quick connect fluid coupling as recited in claim 1, wherein the one or more ribs extend from the exterior end to the interior end.

12. The quick connect fluid coupling as recited in claim 11, wherein the one or more ribs are connected to a flange on the interior end.

13. The quick connect fluid coupling as recited in claim 1, wherein the check valve further comprises:

- a seal arranged proximate the exterior end, wherein in the closed position the exterior end is sealingly engaged with the coupling body; and,
- a plurality of flow paths extending axially between the exterior end and the interior end.

14. The quick connect fluid coupling as recited in claim 13, wherein the seal is arranged to abut against the inlet in the closed position.

15. The quick connect fluid coupling as recited in claim 13, wherein the check valve further comprises an end cap on the external end.

16. The quick connect fluid coupling as recited in claim 15, wherein the end cap is domed. 5

17. The quick connect fluid coupling as recited in claim 15, wherein:

the check valve further comprises a circumferential recess arranged axially between the external end and the end cap; and, 10

the seal is arranged in the recess.

18. The quick connect fluid coupling as recited in claim 15, wherein the end cap comprises a recess extending in an axial direction toward the interior end.

19. The quick connect fluid coupling as recited in claim 15 15
18, wherein the recess comprises a profile that is at least partially concave.

* * * * *