



US006061848A

United States Patent [19][11] **Patent Number:** **6,061,848****Roma et al.**[45] **Date of Patent:** ***May 16, 2000**[54] **AUTOMATIC FUTON FRAME**[75] Inventors: **John K. Roma**, Orchard Park; **James D. Stuart**, Hamburg, both of N.Y.[73] Assignee: **Otis Bed Manufacturing Company, Inc.**, Buffalo, N.Y.

[*] Notice: This patent is subject to a terminal disclaimer.

[21] Appl. No.: **09/080,067**[22] Filed: **May 15, 1998**

4,642,823	2/1987	Wiggins	5/47
4,829,611	5/1989	Fireman et al.	5/47
4,875,244	10/1989	Tremblay	5/37 R
4,937,900	7/1990	Bridges	5/37 R
5,129,114	7/1992	Withers	5/47
5,303,432	4/1994	Fitts	5/37.1
5,345,626	9/1994	Newton	5/37.1
5,485,638	1/1996	Newton	5/37.1
5,513,398	5/1996	Dodge	5/37.1
5,628,076	5/1997	Newton	5/37.1
5,664,268	9/1997	Stoler et al.	5/37.1
5,790,993	8/1998	Roma et al.	5/37.1
5,815,858	10/1998	Dodge	5/37.1
5,940,907	8/1999	Stoler et al.	5/37.1
5,956,785	9/1999	Fireman	5/37.1

Related U.S. Application Data

[63] Continuation-in-part of application No. 08/924,896, Sep. 8, 1997, Pat. No. 5,790,993.

[51] **Int. Cl.⁷** **A47C 17/17; A47C 17/04**[52] **U.S. Cl.** **5/37.1; 5/41; 5/47; 5/927**[58] **Field of Search** **5/37.1, 41, 47, 5/915, 927**[56] **References Cited****U.S. PATENT DOCUMENTS**

656,161	8/1900	Bennett	5/47
2,321,206	6/1943	Holcomb	5/47
2,934,770	5/1960	Willis et al.	5/13
2,972,753	2/1961	Thomas	5/13
3,458,877	8/1969	Edwards	5/43
4,074,371	2/1978	Lindbloom	5/13
4,563,784	1/1986	Shrock et al.	5/37 R
4,625,345	12/1986	Wood	5/13

Primary Examiner—Michael F. Trettel*Assistant Examiner*—Robert G. Santos*Attorney, Agent, or Firm*—Simpson, Simpson & Snyder, L.L.P.

[57]

ABSTRACT

A futon frame includes a seat having a pair of electric motors mounted at opposing sides thereof for driving a pair of pinions arranged to engage inclined toothed racks mounted on each side of the frame for automatically and continuously adjusting the seat and a pivotally connected back between a sofa position and a bed position. The back is connected to opposing sides of the frame by upper and lower follower bearings arranged for travel within corresponding upper and lower guide channels in each opposing side of the frame. A motor controller is mounted to the underside of the seat for connecting a user interface to the motors.


11 Claims, 4 Drawing Sheets

FIG. 1




FIG. 2




FIG. 3




FIG. 4








FIG. 5





AUTOMATIC FUTON FRAME

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of application Ser. No. 08/924,896 filed Sep. 8, 1997, now U.S. Pat. No. 5,790,993.

BACKGROUND

A. Field of the Invention

The present invention relates generally to sofa-bed frames for adjustably supporting a futon mattress, and more particularly to a futon mattress frame having seat and back portions automatically adjustable between a sofa position and a bed position.

B. Description of the Prior Art

Manually operated futon frames having a seat and a back linked to the seat for guided relative motion to permit adjustment between a sofa position and a bed position are well known in the art. In a common futon frame arrangement, the seat and back are pivotally connected to each other, and the back is connected to each adjacent side of the frame by respective link arms having one end pivotally connected to the back and another end pivotally connected to the associated side of the frame. In another common arrangement, pairs of follower bearings extend from the back for travel within corresponding pairs of guide channels provided in each side of the frame. With either type of arrangement, manual adjustment from a sofa position to a bed position is made by sliding the seat forward such that back is caused to follow and assume a horizontal position level with the seat. Manual adjustment from a bed position to a sofa position is carried out by pushing the seat backward at a slight downward angle to force the back into a generally vertical position. U.S. Pat. No. 5,129,114 illustrates this type of construction.

Heretofore, various attempts have been made to automate the adjustment operation of futon frames by providing a single stationary drive motor as means for indirectly driving a follower bracket connected to impart adjustment motion to the seat and back. Examples may be seen in U.S. Pat. Nos. 3,458,877; 4,563,784; and 4,937,900.

A primary challenge encountered in the design of an automatically adjustable futon frame is that of providing means for moving the seat and back from their flat bed position to their angled sofa position against the natural force of gravity. More particularly, a relatively large force is required to initiate backward movement of the seat to dislodge the back from its horizontal position. Prior art automatic frames have typically relied on complex multiple-bar linkages and/or brute power in the electric motor to meet this challenge. Drawbacks of a complex linkage system include added manufacturing cost, increased frame weight, and decreased reliability. Drawbacks of using a single high-powered motor include complexities in the drive train necessary to evenly transmit force to each side of the frame for smooth adjustment motion, with corresponding increase in manufacturing cost. Consequently, despite the long-recognized desirability of an automatically adjustable futon frame, as evidenced by the patents mentioned above, such item is not widely available to consumers at a reasonable price.

SUMMARY OF THE INVENTION

Therefore, it is an object of the present invention to provide an automatically adjustable futon frame which is both reliable and relatively inexpensive to manufacture.

It is a further object of the present invention to provide an automatically adjustable futon frame which adjusts smoothly even when individuals are seated or lying thereon.

In view of these and other objects, an automatically adjustable futon frame formed in accordance with a first embodiment of the present invention comprises a seat and back pivotally connected by a laterally extending hinge and situated between a pair of sides connected by laterally extending front and rear support members underlying the seat and back. A pair of link arms pivotally connect opposite side members of the back to respective sides of the frame.

Dual electric motors are fixed to opposite side members of the seat by mounting brackets, with each motor directly driving a pinion arranged to engage a downwardly facing inclined toothed rack of a rack member secured to an inner surface of the associated side of the frame. A follower pin is also fixed to the mounting bracket for following an upwardly facing inclined guide surface, preferably integral with the rack member, for maintaining drive engagement between the pinion and toothed rack over a predetermined range of travel. A pair of limit switches are arranged near opposite ends of one of the rack members for engagement by the pinion to signal a motor controller to shut-off power to both motors when the seat and back reach a sofa position or a bed position. The motor controller is preferably mounted to the underside of the seat, and a user interface panel for signaling the motor controller allows selective adjustment of the seat and back by a user.

A second and presently preferred embodiment of the present invention is similar to the first embodiment, except that the link arms pivotally connecting opposite side members of the back to respective sides of the frame are removed, and instead each opposite side member of the back is provided with an upper follower bearing and a lower follower bearing received within associated upper and lower guide channels formed in the corresponding side of the frame.

BRIEF DESCRIPTION OF THE DRAWINGS

The nature and mode of operation of the present invention will now be more fully described in the following detailed description of the preferred embodiments taken with the accompanying drawing figures, in which:

FIG. 1 is an isometric view of a futon frame formed in accordance with a first embodiment of the present invention, in its sofa position;

FIG. 2 is a sectional view showing one side of the futon frame depicted in FIG. 1;

FIG. 3 is a view similar to that of FIG. 2, however the futon frame is adjusted to its bed position;

FIG. 4 is a partial view generally similar to that of FIG. 3, but enlarged to show the motor drive arrangement of the present invention in more detail; and

FIG. 5 is a view taken generally along the line 5—5 in FIG. 4.

FIG. 6 is a schematic view showing a second embodiment of the present invention, in its sofa position;

FIG. 7 is a schematic view similar to that of FIG. 6, however showing the frame in its bed position; and

FIG. 8 is a sectional view taken generally along the line 8—8 in FIG. 6.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring initially to FIGS. 1 and 2, a futon frame formed in accordance with a first embodiment of the present inven-

tion is shown and identified generally by the reference numeral **10**. Futon frame **10** is structurally conventional to the extent that it includes a pair of opposite sides **12A,12B** connected by a front support member **14** and a rear support member **16** extending laterally between sides **12A,12B**; a rectangular back **18** situated between sides **12A,12B** and having first and second side members **20A,20B** near respective sides **12A,12B**; a rectangular seat **22** situated between sides **12A,12B** and having first and second side members **24A,24B** near respective sides **12A,12B**, and a hinge **25** fixed along adjacently matched laterally extending members of the back and seat, whereby the back and seat may be folded relative to each other along a laterally extending axis of hinge **25** between a sofa position, shown in FIGS. 1 and 2, and a bed position, shown in FIG. 3.

Referring primarily now to FIGS. 2-4, it will be understood that structure described in general association with side **12B** of frame **10** is also provided with respect to opposite side **12A** in complementary fashion, whereby the present description is simplified by reference only to the structural elements respective of side **12B**, and not to the corresponding structural elements respective of side **12A**. Back **18** is connected to side **12B** by an elongated rigid link arm **26** having one end pivotally connected to back side member **20B** by a pivot pin **28** located at a substantially intermediate point along side member **20B**, and an opposite end pivotally connected to side **12B** by a pivot pin **30** located generally toward the rear of side **12B** above front and rear support members **14** and **16**. Where frame **10** is of wooden construction, a U-shaped metal reinforcement brace **32** is preferably provided to engage three-sides of back side member **20B** about pivot pin **28**, and a metal reinforcement plate **34** is preferably provided on side **12B** about pivot pin **30**.

A unitary rack member **36** is fixed to the inside surface of side **12B** between front and rear support members **14** and **16** and includes an adjustment guide in the form of an upwardly facing straight guide surface **40**, and rack means in the form of a downwardly facing toothed rack **44**. While guide surface **40** and toothed rack **44** of the first embodiment are integrally incorporated into a unitary piece of stock material comprising rack member **36**, a separately formed adjustment guide and rack means may also be employed without straying from the scope of the present invention. Rack member **36** is oriented at an incline relative to ground such that a front end thereof is higher than a rear end thereof and terminates approximately at a level corresponding to upper surfaces **46** and **48** of front and rear support members **14** and **16**, respectively. As will be appreciated from coming description, guide surface **40** defines an inclined travel path, and toothed rack **44** defines an inclined drive path substantially parallel to the travel path.

Referring also now to FIG. 5, it will be seen that a follower pin **50** and automatic drive means **52** are associated with seat **22** for cooperation with adjustment guide surface **40** and toothed rack **44**. Follower pin **50** is fixed relative to seat side member **24B** adjacent an underside thereof by a mounting bracket **56** to which the follower pin may be welded such that it extends from the mounting bracket to engage guide surface **40**. Mounting bracket **56** includes a U-shaped portion **58** secured to seat side member **24B** generally proximate to hinge **25** by conventional fasteners (not shown). Mounting bracket **56** further includes a tail portion **62** extending downwardly from U-shaped portion **58** to which an electric motor **64B** is attached by bolts **66**. Electric motor **64B** drives a pinion **68** arranged to mate with toothed rack **44** via a drive shaft **70** extending through an

opening **72** provided in tail portion **62**. A 24 Volt DC, 33 rpm motor manufactured by Dewert Motorized Systems, Inc. of Frederick, Maryland under part number 002.016 is known to be suitable for use in practicing the present invention, and is chosen to enable automatic adjustment even while individuals are supported by frame **10**.

A motor controller **80** is mounted to the underside of seat **22** generally at the rear center thereof, as may be seen in FIG. 1. The Motor Master 1 controller, 115 Volts AC, 50/60 Hz, 230 Watt Max., Part No. 990.210.002 from Dewert Motorized Systems, Inc., is presently preferred. Motor controller **80** is wired to signal both electric motors **64A,64B** simultaneously. As will be understood, the directions of rotation of motors **64A,64B** must be oppositely set in view of the mirror-image arrangement of the motors. A hard-wired or remote control panel **82** is provided as known in the art to permit user interface with motor controller **80**. A first limit switch **84** wired to controller **80** is fixed to side **12B** near a lower end of rack member **36**, such that driven pinion **68** engages the switch mechanism when seat **22** and back **18** reach their sofa position, thereby signaling controller **80** to shut-off driving current to motors **64A,64B**. A similarly connected limit switch **86** is provided near an upper end of rack member **36** to be engaged by driven pinion **68** when seat **22** and back **18** reach their bed position.

As an added option, an automatic vibrating element **90** may be mounted to back **18** and wired to motor controller **80** to provide frame **10** with a desirable automatic massage feature.

During adjustment of frame **10**, rotating pinion **68** travels along toothed rack **44** while follower pin **50** helps to support seat **22** and maintain pinion **68** in mating engagement with the toothed rack. While the changing orientation of seat **22** causes a corresponding change in the orientation of follower pin **50** and driven pinion **68** relative to rack member **36** due to rotation of mounting bracket **56**, the problem of binding is effectively avoided by locating the centers of follower pin **50** and driven pinion **68** at such an orientation that an imaginary line extending between the centers will be normal to guide surface **40** and toothed rack **44** when the pinion is midway between the ends of the toothed rack during travel, this being the condition of proper alignment between the rack and pinion. The most severe misalignment occurs when the pinion is at either of its travel limits near the ends of rack **44**, thereby splitting the magnitude of misalignment between the ends rather than concentrating misalignment at one end or the other. In this way, slight misalignment at the travel limits may be disregarded in view of normal "play" between rack and pinion. Of course, a specially designed rack member having an arcuate toothed rack may be employed to eliminate binding, however this would increase cost. Finally, link arm **26** enables pivoting reactive adjustment of back **18** in response to movement of hinge **25** as seat **22** is automatically adjusted. The user may stop automatic adjustment at any point between the sofa and bed positions, as desired.

A recently developed and presently preferred futon frame **10'** formed in accordance with a second embodiment of the present invention will be understood with reference to FIGS. 6 through 8. Frame **10'** is similar to the first embodiment described above, except in its manner of connection between back **18** and sides **12A,12B**. Back side members **20A,20B** are each provided with an upper follower bearing **100** arranged for travel within a contoured upper guide channel **104** formed in an adjacent one of the opposing sides **12A, 12B**, and also a lower follower bearing **102** arranged for travel within a contoured lower guide channel **106** formed in the adjacent side **12A** or **12B**.

FIG. 8 shows upper and lower stepped follower bearings 100 and 102 connected to back side member 20B by corresponding upper and lower transversely extending pivot pins 108 and 110. A spacer block 112 is provided between back side member 20B and upper follower bearing 100. Lower pivot pin 110 connects lower follower bearing 102 to back side member 20B, and further provides a pivotal connection between back 18 and seat 22 to replace hinge 25 of the first embodiment, whereby lower follower bearing 102 is coaxial with a transverse pivot axis between back 18 and seat 22. As is apparent, any rear transverse cross-member connecting seat side members 24A and 24B must be moved forward to allow space for overlapped pivoting between back 18 and seat 22. A metal support bracket 114 is located about seat side member 24B as reinforcement at the location where lower pivot pin 110 passes through seat side member 24B. Of course, a corresponding construction is provided with respect to side 12A.

The construction of the second embodiment greatly reduces or eliminates the need for support of the seat by means of follower pin 50 engaging guide surface 40, and also eliminates the need for link arms 26, which may loosen over time.

What is claimed is:

1. An automatically adjustable futon frame comprising:
 - first and second opposing sides connected by front and rear support members extending laterally therebetween, each of said first and second opposing sides having an upper guide channel and a lower guide channel formed therein;
 - a back situated between said first and second opposing sides, said back having first and second side members respectively adjacent to said first and second opposing sides, each of said first and second side members of said back including an upper follower bearing arranged for travel within said upper guide channel of said adjacent opposing side and a lower follower bearing arranged for travel within said lower guide channel of said adjacent opposing side;
 - a seat pivotally connected to said back for folding along a laterally extending axis, said seat having first and second side members;
 - first and second rack means respectively fixed one to each of said first and second opposing sides, said first and second rack means defining a drive path;
 - first and second automatic drive means respectively fixed one to each of said first and second side members of said seat, said first and second automatic drive means each including a driven pinion arranged to engage said first and second rack means, respectively; and
 - controller means connected to said first and second drive means for enabling user operation of said first and second automatic drive means;

whereby said back and seat may be continuously and automatically adjusted relative to each other between a sofa position and a bed position.

2. The futon frame according to claim 1, further comprising first and second adjustment guides respectively fixed one to each of said first and second opposing sides between said front and rear support members, said first and second adjustment guides defining a travel path, a first follower pin fixed relative to said first side member of said seat and arranged to engage said first adjustment guide, and a second follower pin fixed relative to said second side member of said seat and arranged to engage said second adjustment guide.

3. The futon frame according to claim 2, wherein said first adjustment guide and said first rack means are integral portions of a first unitary rack member, and said second adjustment guide and said second rack means are integral portions of a second unitary rack member.

4. The futon frame according to claim 3, wherein each of said first and second rack members includes an upwardly facing guide surface and a downwardly facing toothed rack.

5. The futon frame according to claim 1, wherein said first and second automatic drive means are fixed to said first and second side members of said seat by first and second brackets, respectively.

6. The futon frame according to claim 3, wherein said first follower pin extends from said first bracket to engage said first adjustment guide, and said second follower pin extends from said second bracket to engage said second adjustment guide.

7. The futon frame according to claim 5, wherein said first and second brackets each include a U-shaped portion for engaging an associated side member of said seat along three sides of said associated side member.

8. The futon frame according to claim 3, further including a pair of limit switches connected to said controller means for turning off said first and second automatic drive means when said back and seat reach said sofa position and when said back and seat reach said bed position.

9. The futon frame according to claim 8, wherein said pair of limit switches are fixed to one of said first and second sides near opposite ends of said rack member for engagement by said driven pinion.

10. The futon frame according to claim 1, further comprising automatic vibrating means fixed to said back and connected to said controller means.

11. The futon frame according to claim 1, wherein said lower follower bearing is coaxial with said laterally extending axis.

* * * * *