



US008127905B2

(12) **United States Patent**  
**Kneidel et al.**

(10) **Patent No.:** **US 8,127,905 B2**  
(45) **Date of Patent:** **Mar. 6, 2012**

(54) **SERIES DAMPER WITH HYSTERESIS IN ONE DAMPER**

(75) Inventors: **Craig Kneidel**, Massillon, OH (US);  
**Andre Soto**, Tallmadge, OH (US);  
**Patrick Lindemann**, Wooster, OH (US)

(73) Assignee: **Schaeffler Technologies AG & Co. KG**,  
Herzogenaurach (DE)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 674 days.

5,279,398	A *	1/1994	Graton et al.	192/3.29
5,598,745	A *	2/1997	Tsuchiya	464/68.4
5,752,884	A *	5/1998	Yabe et al.	192/3.29 X
5,813,506	A *	9/1998	Maeda et al.	192/3.29
6,050,376	A *	4/2000	Yabe	192/3.29
6,224,487	B1 *	5/2001	Yuergens	464/68.41
6,244,401	B1	6/2001	Maienschein et al.	
6,439,361	B2	8/2002	Maienschein et al.	
6,695,110	B2	2/2004	Maienschein et al.	
7,073,646	B2 *	7/2006	Sasse et al.	192/3.29
7,222,706	B2 *	5/2007	Tomiyama	192/3.29
7,241,224	B2 *	7/2007	Song et al.	464/64.1
7,481,305	B2 *	1/2009	Sakai et al.	192/3.29
7,658,679	B2 *	2/2010	Avins et al.	192/213.1
7,942,749	B2 *	5/2011	Uehara et al.	464/68.8
2007/0131506	A1 *	6/2007	Wack et al.	192/3.29

(21) Appl. No.: **12/288,859**

(Continued)

(22) Filed: **Oct. 24, 2008**

**FOREIGN PATENT DOCUMENTS**

(65) **Prior Publication Data**

DE 3934798 A1 4/1991

US 2009/0107792 A1 Apr. 30, 2009

(Continued)

**Related U.S. Application Data**

*Primary Examiner* — Gregory Binda  
*Assistant Examiner* — Matthieu Setliff

(60) Provisional application No. 61/000,383, filed on Oct. 25, 2007.

(74) *Attorney, Agent, or Firm* — Simpson & Simpson, PLLC

(51) **Int. Cl.**

**F16H 45/02** (2006.01)

(52) **U.S. Cl.** ..... **192/3.29**; 192/213.2; 192/213.22

(58) **Field of Classification Search** ..... 192/3.28–3.3,  
192/213.2–213.22, 213.1, 213.11, 213.12,  
192/213.3, 213.31; 464/68.4, 68.7, 68.8,  
464/68.3, 68.5, 64.1, 68.41, 38.41

See application file for complete search history.

(57) **ABSTRACT**


A series damper, including: a first damper with a flange and a cover plate; and a second damper with first and second cover plates and a flange. The flange and the cover plate for the first damper are rotationally frictionally engaged and the flange for the second damper rotates free of frictional engagement with the first and second cover plates. The series damper includes a resilient element arranged to cause the frictional engagement of the flange and the cover plate for the first damper. In some aspects, the resilient element is frictionally engaged with the cover plate for the first damper and is arranged to frictionally engage a turbine hub for a torque converter. In some aspects, the resilient element is rotationally connected to the flange for the first damper. In some aspects, the flange for the first damper includes the second cover plate for the second damper.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,347,717	A *	9/1982	Lamarche	192/213.2 X
4,422,535	A *	12/1983	Ling	192/3.28
4,637,500	A	1/1987	Göbel et al.	
4,782,933	A	11/1988	Jäckel et al.	
5,080,215	A	1/1992	Förster et al.	
5,246,399	A *	9/1993	Yanko et al.	192/213.1 X

**12 Claims, 4 Drawing Sheets**



# US 8,127,905 B2

Page 2

---

## U.S. PATENT DOCUMENTS

2007/0251788 A1\* 11/2007 Heck et al. .... 192/3.3  
2008/0257675 A1\* 10/2008 Sasse et al. .... 192/3.29  
2009/0108512 A1\* 4/2009 Soto  
2009/0110475 A1\* 4/2009 Soto et al.  
2009/0125202 A1\* 5/2009 Swank et al. .... 192/3.28  
2009/0139819 A1\* 6/2009 Jameson et al. .... 192/3.29

## FOREIGN PATENT DOCUMENTS

DE 10010953 A1 9/2000  
FR 2526907 11/1983  
FR 2579709 10/1986  
GB 2098702 A 11/1982  
JP 02118256 A \* 5/1990 ..... 192/3.29  
\* cited by examiner




Fig. 1A




Fig. 1B




Fig. 2




Fig. 3




Fig. 4

1

## SERIES DAMPER WITH HYSTERESIS IN ONE DAMPER

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit under 35 U.S.C. §119 (e) of U.S. Provisional Application No. 61/000,383 filed Oct. 25, 2007 which application is incorporated herein by reference.

### FIELD OF THE INVENTION

The invention relates to improvements in apparatus for transmitting force between a rotary driving unit (such as the engine of a motor vehicle) and a rotary driven unit (such as the variable-speed transmission in the motor vehicle). In particular, the invention relates to a series damper with hysteresis between rotating elements in only one of the component dampers in the series damper.

### BACKGROUND OF THE INVENTION

It is known to provide hysteresis forces for both dampers in a series damper. Unfortunately, the prior art does not teach a means for providing a hysteresis force in one damper of a series damper and not in the other damper of the series damper.

Thus, there is a long-felt need to provide a series damper to provide a hysteresis force in only one damper of the series damper.

### BRIEF SUMMARY OF THE INVENTION

The present invention broadly comprises a series damper, including: a first damper with a flange and a cover plate; and a second damper with first and second cover plates and a flange. The flange and cover plate for the first damper are rotationally frictionally engaged and the flange for the second damper rotates free of frictional engagement with the first and second cover plates. The series damper includes a resilient element arranged to cause the frictional engagement of the flange and cover plate for the first damper. In some aspects, the resilient element is frictionally engaged with the cover plate for the first damper and is arranged to frictionally engage a turbine hub for a torque converter. In some aspects, the resilient element is rotationally connected to the flange for the first damper. In some aspects, the flange for the first damper includes the second cover plate for the second damper.

In some aspects, the cover plate for the first damper includes at least one slot, the flange for the first damper includes at least one protrusion at least partially disposed in the at least one slot, and there is lash between the cover plate for the first damper and the at least one protrusion in the at least one slot. In some aspects, the frictional engagement between the flange and cover plate for the first damper occurs during windup of the first damper.

In some aspects, the series damper includes an annular element rotationally connected to the flange for the first damper, and the resilient element urges the annular element against the cover plate for the first damper. In some aspects, the resilient element is rotationally connected to the cover plate for the first damper.

It is a general object of the present invention to provide a series damper to provide a hysteresis force in only one damper of the series damper.

2

These and other objects and advantages of the present invention will be readily appreciable from the following description of preferred embodiments of the invention and from the accompanying drawings and claims.

### BRIEF DESCRIPTION OF THE DRAWINGS

The nature and mode of operation of the present invention will now be more fully described in the following detailed description of the invention taken with the accompanying drawing figures, in which:

FIG. 1A is a perspective view of a cylindrical coordinate system demonstrating spatial terminology used in the present application;

FIG. 1B is a perspective view of an object in the cylindrical coordinate system of FIG. 1A demonstrating spatial terminology used in the present application;

FIG. 2 is a partial cross-sectional view of a present invention series damper in a torque converter;

FIG. 3 is a partial perspective detail view of area 3 in FIG. 2; and,

FIG. 4 is a partial cross-sectional view of a present invention series damper in a torque converter.

### DETAILED DESCRIPTION OF THE INVENTION

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements of the invention. While the present invention is described with respect to what is presently considered to be the preferred aspects, it is to be understood that the invention as claimed is not limited to the disclosed aspects.

Furthermore, it is understood that this invention is not limited to the particular methodology, materials and modifications described and as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the present invention, which is limited only by the appended claims.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this invention belongs. Although any methods, devices or materials similar or equivalent to those described herein can be used in the practice or testing of the invention, the preferred methods, devices, and materials are now described.

FIG. 1A is a perspective view of cylindrical coordinate system 80 demonstrating spatial terminology used in the present application. The present invention is at least partially described within the context of a cylindrical coordinate system. System 80 has a longitudinal axis 81, used as the reference for the directional and spatial terms that follow. The adjectives "axial," "radial," and "circumferential" are with respect to an orientation parallel to axis 81, radius 82 (which is orthogonal to axis 81), and circumference 83, respectively. The adjectives "axial," "radial" and "circumferential" also are regarding orientation parallel to respective planes. To clarify the disposition of the various planes, objects 84, 85, and 86 are used. Surface 87 of object 84 forms an axial plane. That is, axis 81 forms a line along the surface. Surface 88 of object 85 forms a radial plane. That is, radius 82 forms a line along the surface. Surface 89 of object 86 forms a circumferential plane. That is, circumference 83 forms a line along the surface. As a further example, axial movement or disposition is parallel to axis 81, radial movement or disposition is par-

3

allel to radius **82**, and circumferential movement or disposition is parallel to circumference **83**. Rotation is with respect to axis **81**.

The adverbs “axially,” “radially,” and “circumferentially” are with respect to an orientation parallel to axis **81**, radius **82**, or circumference **83**, respectively. The adverbs “axially,” “radially,” and “circumferentially” also are regarding orientation parallel to respective planes.

FIG. 1B is a perspective view of object **90** in cylindrical coordinate system **80** of FIG. 1A demonstrating spatial terminology used in the present application. Cylindrical object **90** is representative of a cylindrical object in a cylindrical coordinate system and is not intended to limit the present invention in any manner. Object **90** includes axial surface **91**, radial surface **92**, and circumferential surface **93**. Surface **91** is part of an axial plane, surface **92** is part of a radial plane, and surface **93** is part of a circumferential plane.

FIG. 2 is a partial cross-sectional view of present invention series damper **100** in torque converter **102**.

FIG. 3 is a partial perspective detail view of area **3** in FIG. 2. The following should be viewed in light of FIGS. 2 and 3. Series damper **100** includes dampers **104** and **106**. Damper **104** includes cover plates **108** and **110** and flange **112**. Damper **106** includes cover plates **114** and **116** and flange **118**. Flange **112** and cover plate **116** are continuous. That is, flange **112** includes plate **116** and plate **116** includes flange **112**. As further described infra, flange **112** (plate **116**) is rotationally frictionally engaged with cover **110**. That is, damper **104** includes frictional engagement among the constituent cover plates and flange for damper **104**. However, plate **114** and flange **118** rotate substantially free of frictional engagement. For example, flange **118** is not rotationally frictionally engaged with cover plate **114** or plate **116**. Thus, as further described infra, hysteresis forces are only applied to damper **104**.

In some aspects, cover plate **116** includes at least one axial protrusion **120** disposed in a respective slot **122** in plate **110**. The circumferential length **124** of the protrusion is less than the circumferential extent **126** of the slot. That is, there is lash between plate **110** and protrusion **120**. Resilient element **128** includes at least one radial protrusion **130** interlocked with protrusions **120**. Any resilient element known in the art can be used for element **128**. In general, protrusions **120** and **130** rotationally connect plate **116** and the resilient element. By rotationally connect, or secure, we mean that the plate and the resilient element are connected such that the two components rotate together, that is, the two components are fixed with respect to rotation. Rotationally connecting two components does not necessarily limit relative movement in other directions. For example, it is possible for two components that are rotationally connected to have axial movement with respect to each other via a spline connection. However, it should be understood that rotational connection does not imply that movement in other directions is necessarily present. For example, two components that are rotationally connected can be axially fixed one to the other. The preceding explanation of rotational connection is applicable to the discussions infra.

Resilient element **128** is preloaded during assembly of torque converter **102** so that the element reacts against plate **110** and turbine hub **132**. That is, the element is forced against plate **110** and the hub. As noted supra, length **126** is greater than **124**; therefore, plate **116** is partially rotatable with respect to plate **110**. For example, plate **116** is rotatable in direction **134** until edge **136** contacts edge **138**. This partial rotation occurs during wind-up of damper **104**. Thus during wind-up of damper **104**, the resilient element provides a hysteresis, or frictional, force between cover **116** (rotationally

4

connected to the resilient element) and cover **110** and between cover **116** and the hub. At the same time, damper **106** operates without rotational friction between plates **114** and **116** and flange **118**.

FIG. 4 is a partial cross-sectional view of present invention series damper **200** in torque converter **202**. Series damper **200** includes dampers **204** and **206**. Damper **204** includes cover plates **208** and **210** and flange **212**. Damper **206** includes cover plates **214** and **216** and flange **218**. Flange **212** and cover plate **216** are continuous. That is, flange **212** includes plate **216** and plate **216** includes flange **212**. As further described infra, flange **212** (plate **216**) is rotationally frictionally engaged with cover **210**. That is, damper **204** includes frictional engagement among the constituent cover plates and flange for damper **204**. However, plate **214** and flange **218** rotate free of frictional engagement. For example, flange **218** is not rotationally frictionally engaged with cover plate **214** or plate **216**. Thus, hysteresis forces are only applied to damper **204**.

Damper **200** includes resilient element **220** and ring, or annular, element **222**. Any resilient element known in the art can be used for element **220**. The ring element is rotationally connected to plate **216** by any means known in the art, for example, splines and slots in plate **216** and the ring element, respectively. However, the ring element can be moved axially with respect to plate **216**. In some aspects, the resilient element is fixedly secured to plate **210**, which is fixed to turbine hub **224**, by any means known in the art, for example, rivets **226**. In some aspects (not shown), the resilient element is fixed directly to the hub. The resilient element urges the ring element in direction **228**, which brings the ring element into frictional contact with plate **210**. Thus, resilient element **220** causes a frictional, or hysteresis, force between flange **212** (plate **216**) and plate **210**. At the same time, damper **206** operates without rotational friction between plates **214** and **216** and flange **218**.

The following should be viewed in light of FIGS. 2-4. In some aspects, the friction in damper **104** or **204** is with respect to an inner cover plate (plates **110** and **210**, respectively), that is, the cover plate facing the respective torus for the respective torque converter. In some aspects (not shown), the friction in damper **104** or **204** is with respect to an outer cover plate (plates **108** and **208**, respectively), that is, the cover plate facing a respective cover for the respective torque converter.

Thus, it is seen that the objects of the present invention are efficiently obtained, although modifications and changes to the invention should be readily apparent to those having ordinary skill in the art, which modifications are intended to be within the spirit and scope of the invention as claimed. It also is understood that the foregoing description is illustrative of the present invention and should not be considered as limiting. Therefore, other embodiments of the present invention are possible without departing from the spirit and scope of the present invention.

What we claim is:

1. A series damper, including:

- a lock-up clutch;
- a first damper with a flange, a cover plate, and a spring engaged with the flange and the cover plate; and,
- a second damper with first and second cover plates and a flange, wherein:
  - the flange and cover plate for the first damper are rotationally frictionally engaged at a point radially inward of the at least one spring;
  - the flange for the second damper rotates free of frictional engagement with the first and second cover plates; and,



5

- a torque path from the clutch to the second damper passes through the first damper.
- 2. The series damper of claim 1 including a resilient element arranged to cause the frictional engagement of the flange and cover plate for the first damper.
- 3. The series damper of claim 2 wherein the resilient element is frictionally engaged with the cover plate for the first damper and is arranged to frictionally engage a turbine hub for a torque converter.
- 4. The series damper of claim 3 wherein the frictional engagement between the flange and cover plate for the first damper occurs during windup of the first damper.
- 5. The series damper of claim 2 wherein the resilient element is rotationally connected to the flange for the first damper.
- 6. The series damper of claim 2 including an annular element rotationally connected to the flange for the first damper, and wherein the resilient element urges the annular element against the cover plate for the first damper.
- 7. The series damper of claim 6 wherein the resilient element is rotationally connected to the cover plate for the first damper.
- 8. The series damper of claim 6 wherein the flange for the first damper includes the second cover plate for the second damper.
- 9. The series damper of claim 1 wherein the cover plate for the first damper includes at least one slot, the flange for the first damper includes at least one protrusion at least partially disposed in the at least one slot, and there is lash between the cover plate for the first damper and the at least one protrusion in the at least one slot.

6

- 10. The series damper of claim 1 wherein the flange for the first damper includes the second cover plate for the second damper.
- 11. A torque converter, including:
  - a first damper with a cover plate and a flange;
  - a second damper with first and second cover plates and a flange, the flange for the first damper including the first cover plate for the second damper;
  - a turbine hub; and,
  - a resilient element rotationally connected to the flange for the first damper and frictionally engaged with the cover plate for the first damper and the turbine hub, wherein the flange for the second damper rotates free of frictional engagement with the first and second cover plates.
- 12. A torque converter, including:
  - a first damper with a cover plate and a flange;
  - a second damper with first and second cover plates and a flange, the flange for the first damper including the first cover plate for the second damper;
  - an annular element rotationally connected to the flange for the first damper; and,
  - a resilient element rotationally connected to the cover plate for the first damper and urging the annular element against the cover plate for the first damper to frictionally engage the flange and the cover plate for the first damper, wherein the flange for the second damper rotates free of frictional engagement with the first and second cover plates.

\* \* \* \* \*