



US008746424B2

(12) **United States Patent**  
**Kneidel**

(10) **Patent No.:** **US 8,746,424 B2**  
(45) **Date of Patent:** **Jun. 10, 2014**

(54) **COIL SPRING TILGER DAMPER FIXED TO TURBINE**

(56) **References Cited**

(75) Inventor: **Craig Kneidel**, Massillon, OH (US)  
(73) Assignee: **Schaeffler Technologies GmbH & Co. KG**, Herzogenaurach (DE)

U.S. PATENT DOCUMENTS

2007/0131506 A1\* 6/2007 Wack et al. .... 192/3.29  
2009/0125202 A1 5/2009 Swank et al.  
2011/0192692 A1 8/2011 Werner et al.  
2011/0247322 A1\* 10/2011 Lindemann et al. .... 60/338

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 281 days.

FOREIGN PATENT DOCUMENTS

DE 102007057431 6/2009  
DE 102009042837 4/2010  
DE 102009052202 6/2010  
WO 2010063251 6/2010  
WO 2011076168 6/2011  
WO 2011122130 10/2011

(21) Appl. No.: **13/238,230**

(22) Filed: **Sep. 21, 2011**

(65) **Prior Publication Data**

US 2012/0073925 A1 Mar. 29, 2012

**Related U.S. Application Data**

(60) Provisional application No. 61/385,689, filed on Sep. 23, 2010.

(51) **Int. Cl.**  
**F16H 45/02** (2006.01)  
**F16H 41/24** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **192/3.29**; 192/213.2

(58) **Field of Classification Search**  
USPC ..... 60/338; 192/213.2  
See application file for complete search history.

\* cited by examiner


*Primary Examiner* — Rodney Bonck

(74) *Attorney, Agent, or Firm* — Simpson & Simpson, PLLC

(57) **ABSTRACT**

A torque converter, including: a turbine with a turbine shell; and a damper assembly including: an output flange; a first cover plate; a first drive plate fixedly secured to the turbine shell; a first plurality of springs engaged with the first cover plate; a second plurality of springs engaged with the first cover plate and the output flange; a third plurality of springs engaged with the first cover plate and the first drive plate; and a single torque path from the turbine shell to the damper assembly, the single torque path formed by the first drive plate.

**14 Claims, 5 Drawing Sheets**






Fig. 1A




Fig. 1B




Fig. 2




Fig. 3




Fig. 4




Fig. 5

## COIL SPRING TILGER DAMPER FIXED TO TURBINE

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit under 35 U.S.C. §119 (e) of U.S. Provisional Application No. 61/385,689 filed on Sep. 23, 2010 which application is incorporated herein by reference.

### FIELD OF THE INVENTION

The present disclosure relates to a damper assembly for a torque converter using inertia from a turbine to damper vibration. In particular, the present disclosure relates to a damper assembly for a torque converter with an additional plate fixed to the turbine.

### BACKGROUND OF THE INVENTION

Commonly owned U.S. Patent Application Publication 2009/0125202 teaches a damper assembly in a torque converter with a cover plate fixed axially but not rotationally to a turbine, and a damper fixed to the turbine and the cover plate.

### BRIEF SUMMARY OF THE INVENTION

According to aspects illustrated herein, there is provided a torque converter, including: a turbine with a turbine shell; and a damper assembly including: an output flange; a first cover plate; a first drive plate fixedly secured to the turbine shell; a first plurality of springs engaged with the first cover plate; a second plurality of springs engaged with the first cover plate and the output flange; a third plurality of springs engaged with the first cover plate and the first drive plate; and a single torque path from the turbine shell to the damper assembly, the single torque path formed by the first drive plate.

According to aspects illustrated herein, there is provided a torque converter, including: a cover; a turbine with a turbine shell; a lock up clutch including a piston plate, friction material, and a first drive plate; and a damper assembly including: an output flange; a cover plate; a second drive plate fixedly secured to the turbine shell; a first plurality of springs engaged with the cover plate and the second drive plate; a second plurality of springs engaged with the cover plate and the output flange and circumferentially aligned with the first plurality of springs; and a third plurality of springs engaged with the cover plate and the first drive plate.

According to aspects illustrated herein, there is provided a torque converter, including: a turbine with a turbine shell and a damper assembly. The damper assembly includes: an output flange; a cover plate; a first plurality of springs engaged with the cover plate; a second plurality of springs engaged with the cover plate and the output flange; a third plurality of springs, separate from the first and second pluralities of springs; a single torque path from the turbine shell to the damper assembly; a first torque path from the first plurality of springs to the output flange via the cover plate; a second torque path from the third plurality of springs to the cover plate; and a solid torque path, including the single torque path, from the turbine shell to the third plurality of springs.

These and other objects and advantages of the present invention will be readily appreciable from the following description of the invention and from the accompanying drawings and claims.

## BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments are disclosed, by way of example only, with reference to the accompanying schematic drawings in which corresponding reference symbols indicate corresponding parts, in which:

FIG. 1A is a perspective view of a cylindrical coordinate system demonstrating spatial terminology used in the present application;

FIG. 1B is a perspective view of an object in the cylindrical coordinate system of FIG. 1A demonstrating spatial terminology used in the present application;

FIG. 2 is a partial cross-sectional view of a torque converter with a damper assembly and drive plate connected to a turbine and fasteners as rotational stops for the drive plate;

FIG. 3 is a back view of a portion of the damper assembly shown in FIG. 2;

FIG. 4 is a partial cross-sectional view of a torque converter with a damper assembly and drive plate connected to a turbine and tabs on the drive plate as rotational stops for the drive plate; and,

FIG. 5 is a partial cross-sectional view of a torque converter with a damper assembly and drive plate connected to a turbine with radially intermediate springs.

### DETAILED DESCRIPTION OF THE INVENTION

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements of the invention. It is to be understood that the invention as claimed is not limited to the disclosed aspects.

Furthermore, it is understood that this invention is not limited to the particular methodology, materials and modifications described and as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the present invention, which is limited only by the appended claims.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this invention belongs. Although any methods, devices or materials similar or equivalent to those described herein can be used in the practice or testing of the invention, the preferred methods, devices, and materials are now described.

FIG. 1A is a perspective view of cylindrical coordinate system **80** demonstrating spatial terminology used in the present application. The present invention is at least partially described within the context of a cylindrical coordinate system. System **80** has a longitudinal axis **81**, used as the reference for the directional and spatial terms that follow. The adjectives “axial,” “radial,” and “circumferential” are with respect to an orientation parallel to axis **81**, radius **82** (which is orthogonal to axis **81**), and circumference **83**, respectively. The adjectives “axial,” “radial” and “circumferential” also are regarding orientation parallel to respective planes. To clarify the disposition of the various planes, objects **84**, **85**, and **86** are used. Surface **87** of object **84** forms an axial plane. That is, axis **81** forms a line along the surface. Surface **88** of object **85** forms a radial plane. That is, radius **82** forms a line along the surface. Surface **89** of object **86** forms a circumferential plane. That is, circumference **83** forms a line along the surface. As a further example, axial movement or disposition is parallel to axis **81**, radial movement or disposition is par-

3

allel to radius **82**, and circumferential movement or disposition is parallel to circumference **83**. Rotation is with respect to axis **81**.

The adverbs “axially,” “radially,” and “circumferentially” are with respect to an orientation parallel to axis **81**, radius **82**, or circumference **83**, respectively. The adverbs “axially,” “radially,” and “circumferentially” also are regarding orientation parallel to respective planes.

FIG. 1B is a perspective view of object **90** in cylindrical coordinate system **80** of FIG. 1A demonstrating spatial terminology used in the present application. Cylindrical object **90** is representative of a cylindrical object in a cylindrical coordinate system and is not intended to limit the present invention in any manner. Object **90** includes axial surface **91**, radial surface **92**, and circumferential surface **93**. Surface **91** is part of an axial plane, surface **92** is part of a radial plane, and surface **93** is a circumferential surface.

FIG. 2 is a partial cross-sectional view of torque converter **100** with a damper assembly and drive plate connected to a turbine and fasteners as rotational stops for the drive plate.

FIG. 3 is a back view of a portion of damper assembly **102** shown in FIG. 2. The following should be viewed in light of FIGS. 2 and 3. Torque converter **100** includes damper assembly **102**, lock up clutch **104**, and turbine **106** with turbine shell **108**. The damper assembly includes output flange **110**, cover plates **112** and **114**, and drive plate **116** fixedly secured to the turbine shell. Drive plate **116** can be fixed to the turbine by any means known in the art, for example, rivets **118**. Radially inward portion **120** of flange **110** is configured to engage an input shaft (not shown), for example, for a transmission.

The damper assembly also includes: plurality of springs **122** engaged with cover plate **112** and the lock up clutch; plurality of springs **124** engaged with cover plates **112** and **114**, and the output flange; and plurality of springs **126** engaged with cover plates **112** and **114**, and drive plate **116**. Springs **126** can be referred to as turbine tilger springs. In one embodiment springs **124** and **126** are at a same radial distance **128** from axis of rotation **130** for the torque converter and plurality **122** is disposed radially outward from pluralities **124** and **126**.

The torque converter includes cover **132** and the lock up clutch includes axially displaceable piston plate **134** and friction material **136**. Specifically, radially outward portion **138** of the piston plate is axially displaceable such that in an engaged position for the clutch the friction material is engaged with, or in contact with, the cover and the piston plate and torque is transferable from the cover to the piston plate. The lock up clutch is directly engaged with, or in contact with, springs **122**. In one embodiment, the lock up clutch includes drive plate **140** fixedly connected to the piston plate by any means known in the art, for example, rivets **141**, such that drive plate **140** rotates with the piston plate. Drive plate **140** is in direct contact with spring **122**.

In one embodiment, portion **142** of drive plate **116** is disposed axially between the output flange and cover plate **112**. Drive plate **116** is rotatable relative to the flange and the cover plates **112** and **114**. In one embodiment, rotation of drive plate **116** is restricted by fasteners **144**, for example, sheet metal rivets, connecting cover plates **112** and **114**. For example, drive plate **116** includes slots or notches **146** and fasteners **144** pass through the slots. To simplify the presentation, a single slot is shown; however, it should be understood that any number of slots **146** can be present in plate **116**. The slots have respective circumferential ends **146A** and **146B** and if drive plate **116** rotates sufficiently in rotational direction **R1** or **R2**, the respective ends contact the fasteners, the rotation of the plate is halted, and if force is applied to drive plate **116** in the

4

same rotational direction, springs **124** continue to compress. For example, if drive plate **116** rotates sufficiently in rotational direction **R1**, ends **146B** contact the fasteners, the rotation of the plate is halted, and if force is applied to drive plate **116** in direction **R1**, springs **124** continue to compress.

FIG. 4 is a partial cross-sectional view of torque converter **100** with a damper assembly and drive plate connected to a turbine and tabs on the drive plate as rotational stops for the drive plate. In one embodiment, portion **142** of the drive plate is disposed axially between the output flange and cover plate **112**. Drive plate **116** is rotatable relative to the flange and the cover plates **112** and **114**. In one embodiment, rotation of drive plate **116** is restricted by tabs, or axial extensions, **148** on drive plate **116**. For example, cover plate **112** includes slots **150** and tabs **148** are disposed in the slots. The slots have respective circumferential ends and if drive plate **116** rotates sufficiently in either rotational direction, the respective ends contact the tabs, the rotation of the plate is halted, and if force is applied to drive plate **116** in the same rotational direction, springs **124** continue to compress.

Returning to FIG. 3, respective ends of springs **126** are engaged with slots **152** in drive plate **116**. In FIG. 3, the springs are engaged with ends **154** of slots **152**. The other respective ends of springs **126** are engaged with slots **156** in cover plate **114**. Springs **124** are engaged with slots **158** and **160** in cover plate **114** and the output flange, respectively. In one embodiment, slots **158** and **160** have essentially the same dimensions and are axially aligned in a rest position for the damper assembly.

FIG. 5 is a partial cross-sectional view of torque converter **100** with a damper assembly and drive plate connected to a turbine with radially intermediate springs. In one embodiment, springs **126** are engaged with cover plate **112** and drive plate **116** and are disposed radially between springs **122** and **124**. In one embodiment, portion **142** of drive plate **116** is disposed axially between the output flange and cover plate **112**. Drive plate **116** is rotatable relative to the flange and cover plates **112** and **114**. In one embodiment, rotation of drive plate **116** is restricted by fasteners **144**, for example, rivets, connecting the cover plates **112** and **114**. For example, drive plate **116** includes slots **146** and fasteners **144** pass through slots **146**. Slots **146** have respective circumferential ends and if drive plate **116** rotates sufficiently in either rotational direction, the respective ends contact the fasteners, the rotation of the plate is halted, and if force is applied to drive plate **116** in the same rotational direction, springs **124** continue to compress.

Advantageously, the arrangement of FIG. 5 enables an increase in the number of springs **124** and/or **126** in the damper assembly. For example, circumferential space occupied by springs **126** in FIGS. 2 through 4 is available for additional springs **124**, since springs **126** are disposed radially between springs **122** and **124**. Increasing the number of springs **124** improves the performance of the damper assembly. Further, the spaces occupied by springs **124** in FIGS. 2 through 4 is available for additional springs **126** if desired.

The following should be viewed in light of FIGS. 2 through 5. Damper assembly **102** includes opposed pairs of coil springs **126**, for example, springs **126A** and **126B**, preloaded such that there is a zero total pre-toad on plate **116**. Plate **116** drives springs **126**. In one embodiment, inner damper **162** of the double damper configuration of damper **102** is split into two function portions. The turbine tilger damper portion of the split damper, using the cover plates and plate **116**, is used for the turbine tilger springs. The other portion of the split damper, including the cover plates and the flange, is used for the main stage of the damper wind-up and springs **124**.



## 5

In FIG. 3, four springs **124** and four springs **126** are shown. However, it should be understood that torque converter **100** is not limited to any particular number of springs **124** and **126**. The actual number of springs **124** and **126** used could depend on the envelope and the torque requirements for a particular design of torque converter **100**. The concept shown is intended to illustrate the concept of the tilger riveted intermediate drive plate. An example, of the function of the design illustrated in the present disclosure is shown by torque path **164** in FIG. 4. Torque is transmitted to the cover and enters the damper through the lock up clutch and plate **140** to wind up cover plates **112** and **114**. The torque then winds up the main stage inner damper springs **124**, which then transmit the torque to the flange.

During operation, the turbine inertia as embodied by the turbine shell and plate **116**, is connected to portion **162** via plate **116** and springs **126**. Thus, a torque converter of the present disclosure advantageously links inertia for a turbine with a damper assembly and uses the inertia to cancel undesirable vibrations associated with an engine connected to the torque converter. For example, the vibrations and inertia of the turbine can be tuned to be out of phase with vibrations from an engine connected to the torque converter. In one embodiment, the turbine tilger damper portion requires a wind-up stop. As noted supra, a wind-up stop is provided by fasteners **144** and slots in plate **116** or by tabs **148** and slots in cover plate **112**.

The operation of torque converter **100** noted above also can be described in terms of the torque paths shown in FIGS. 2 and 3. For example, torque path **166** is from springs **122** to flange **110** via cover plates **112** and **114**. Solid torque path **168** is from the turbine shell to springs **126** and torque path **170** is from springs **126** to cover plates **112** and **114**. By solid torque path we mean that the path does not include any elements, for example, springs or flexion devices, that would attenuate or absorb the torque. That is, the torque path is equivalent to solid piece of material joining the turbine shell and springs **126**, for example, the torque path is formed by plate **116** fixed to the turbine shell. Torque transmitted along path **166** encounters torque transmitted along torque paths **168** and **170**. Thus, for example, torque along path **166** can urge cover plates **112** and **114** in one direction, which in turn can urge the output flange in that direction. If the torque takes the form of a surge or spike, such displacement of the flange can be undesirable. However, torque along paths **168** and **170** can urge cover plates **112** and **114** in the opposite rotational direction, advantageously dissipating or attenuating an undesirable spike along path **166**.

The turbine tilger configuration of the present disclosure provides advantages for manufacturing by making the assembly process easier and by eliminating the need for additional welds or rivets to accommodate the turbine tilger damper portion. The entire damper **102**, including the turbine tilger damper portion, can be riveted in a single operation with fasteners, for example, rivets, **144**, which are used to connect the cover plates. During the riveting process, the tilger springs can be accessed by the assembly carrier. This access allows the use of assembly pins to preload the tilger springs, making the assembly of the driving intermediate plate possible. Finally, since the damper and turbine tilger is formed as a single riveted unit, it can be riveted to the turbine during the upset of the already-existing turbine fastener, for example, rivet **118**. Thus, a torque converter of the present disclosure advantageously eliminates the need for a separate welded tab/ring on the turbine shell and eliminates the need for a preload spacer plate by providing a simpler method for assembly. A torque converter of the present disclosure also

## 6

eliminates the need for any additional riveting operations or welds, which are required with prior art designs.

Thus, it is seen that the objects of the present invention are efficiently obtained, although modifications and changes to the invention should be readily apparent to those having ordinary skill in the art, which modifications are intended to be within the spirit and scope of the invention as claimed. It also is understood that the foregoing description is illustrative of the present invention and should not be considered as limiting. Therefore, other embodiments of the present invention are possible without departing from the spirit and scope of the present invention.

What I claim is:

1. A torque converter, comprising:

a turbine with a turbine shell; and,

a damper assembly including:

an output flange;

a first cover plate;

a first drive plate fixedly secured to the turbine shell;

a first plurality of springs engaged with the first cover plate;

a second plurality of springs engaged with the first cover plate and the output flange and free of engagement with the first drive plate;

a third plurality of springs engaged with the first cover plate and the first drive plate and free of engagement with the output flange; and,

a single torque path from the turbine shell to the damper assembly, the single torque path formed by the first drive plate.

2. The torque converter of claim 1 wherein the second and third pluralities of springs are at a same radial distance from an axis of rotation for the torque converter.

3. The torque converter of claim 1 wherein the second and third pluralities of springs are circumferentially aligned.

4. The torque converter of claim 1 wherein the third plurality of springs is disposed radially outward from the second plurality of springs.

5. The torque converter of claim 1 wherein the third plurality of springs is disposed radially between the first and second pluralities of springs.

6. The torque converter of claim 1 further comprising:

a cover; and,

a lock up clutch engageable with the cover and directly engaged with the first plurality of springs.

7. The torque converter of claim 6 wherein:

the lock up clutch includes an axially displaceable piston plate and a second drive plate connected to the piston plate such that the second drive plate rotates when the piston plate rotates; and,

the second drive plate is in direct contact with the first plurality of springs.

8. The torque converter of claim 1 wherein a portion of the first drive plate is disposed axially between the flange and the first cover plate.

9. The torque converter of claim 1 wherein the first drive plate is rotatable relative to the flange and the first cover plate.

10. The torque converter of claim 1 wherein:

the damper assembly includes a second cover plate connected to the first cover plate by a plurality of fasteners; and,

rotation of the first drive plate is restricted by the plurality of fasteners.

11. The torque converter of claim 1 wherein:

the first cover plate includes a slot;

the first drive plate includes an axial protrusion disposed in the slot; and,

7

the rotation of the first drive plate is restricted by contact of the axial protrusion with respective ends of the slot.

**12.** A torque converter, comprising:

- a cover;
- a turbine with a turbine shell; 5
- a lock up clutch including a piston plate, friction material, and a first drive plate; and,
- a damper assembly including:
  - an output flange; 10
  - a cover plate;
  - a second drive plate fixedly secured to the turbine shell;
  - a first plurality of springs engaged with the cover plate and the second drive plate;
  - a second plurality of springs engaged with the cover plate and the output flange and circumferentially aligned with the first plurality of springs; and, 15
  - a third plurality of springs engaged with the cover plate and the first drive plate, wherein a portion of the second drive plate is disposed axially between the flange and the cover plate. 20

**13.** A torque converter, comprising:

- a turbine with a turbine shell; and,
- a damper assembly including:
  - an output flange; 25
  - a cover plate;

8

- a first plurality of springs engaged the cover plate and located at a first radial distance from an axis of rotation for the torque converter;
  - a second plurality of springs engaged with the cover plate and the output flange and located at a second radial distance from an axis of rotation for the torque converter;
  - a third plurality of springs, separate from the first and second pluralities of springs and located at a third radial distance, less than the first radial distance and greater than the second radial distance, from an axis of rotation for the torque converter;
  - a single torque path from the turbine shell to the damper assembly;
  - a first torque path from the first plurality of springs to the output flange via the cover plate;
  - a second torque path from the third plurality of springs to the cover plate; and,
  - a solid torque path, including the single torque path, from the turbine shell to the third plurality of springs.
- 14.** The torque converter of claim **13** wherein:
- first torque transmitted along the first torque path urges the cover in a first rotational direction; and,
  - second torque transmitted along the second torque path urges the cover in a second rotational direction, opposite the first rotational direction.

\* \* \* \* \*