



US008992333B2

(12) **United States Patent**
Blough

(10) **Patent No.:** **US 8,992,333 B2**
(45) **Date of Patent:** **Mar. 31, 2015**

(54) **FOLDOVER TAB FOR RETAINER SPRING STOP**

(71) Applicant: **Schaeffler Technologies AG & Co. KG**,
Herzogenaurach (DE)

(72) Inventor: **Gregory Blough**, Wooster, OH (US)

(73) Assignee: **Schaeffler Technologies GmbH & Co. KG**,
Herzogenaurach (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/898,981**

(22) Filed: **May 21, 2013**

(65) **Prior Publication Data**

US 2013/0324267 A1 Dec. 5, 2013

Related U.S. Application Data

(60) Provisional application No. 61/653,135, filed on May 30, 2012.

(51) **Int. Cl.**
F16F 15/121 (2006.01)
F16F 15/123 (2006.01)

(52) **U.S. Cl.**
CPC **F16F 15/1213** (2013.01); **F16F 15/1232** (2013.01)
USPC **464/68.92**; 464/67.1

(58) **Field of Classification Search**
USPC 464/66.1, 67.1, 68.8–68.92; 192/3.29, 192/203, 205

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,903,803	A *	2/1990	Koshimo	192/205 X
6,290,042	B1	9/2001	Breier	
7,207,888	B2 *	4/2007	Verhoog et al.	464/67.1
7,585,226	B2	9/2009	Uhler et al.	
7,717,242	B2	5/2010	Schrader et al.	
7,753,183	B2	7/2010	Parks et al.	

* cited by examiner



Primary Examiner — Gregory Binda



(74) *Attorney, Agent, or Firm* — Simpson & Simpson, PLLC

(57) **ABSTRACT**

A vibration damper, including a cover plate with an annular portion, and a spring portion including spring retaining portions forming respective spaces and a spring blocking portions including respective protrusion segments and respective tab segments including respective portions of an edge of the cover plate and having a same first thickness. The damper includes springs at least partially located in the respective spaces, and having respective longitudinal ends, and a second cover plate or output flange connected to the cover plate. The springs are arranged to transmit torque to the cover plate. The respective protrusion segments have a same second thickness and include respective protrusions. Respective first portions of the longitudinal ends of the springs are engaged with the respective protrusions. Respective second portions of the longitudinal ends of the springs are engaged with the respective tab segments.

8 Claims, 7 Drawing Sheets








Fig 2




Fig. 3




Fig. 3A




Fig. 3B




Fig. 4A




Fig. 4B




Fig. 5A




Fig. 5B




Fig. 6

1

FOLDOVER TAB FOR RETAINER SPRING STOP

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit under 35 U.S.C. §119 (e) of U.S. Provisional Patent Application No. 61/653,135 filed May 30, 2012.

TECHNICAL FIELD

The present disclosure relates to a spring retaining configuration for a cover in a vibration damper, in particular, a tab for engaging springs ends formed by folding a portion of the cover.

BACKGROUND

FIG. 6 is a partial cross-sectional view of a prior art torque converter and vibration damper. Torque converter **200** includes cover **202** arranged to receive torque, vibration damper **204**, torque converter clutch **206**, and output **208**. The vibration damper includes input component **210**, at least one spring **212**, and cover plate **214**. The damper also includes cover plate **216** fixedly secured to cover plate **214**, at least one spring **218**, and flange **220** forming output **208**. The at least one spring **218** is engaged with cover plates **214** and **216**, and the flange. The input component is connected to the torque converter clutch. The clutch is controllable to connect and disconnect the cover to and from the vibration damper. Springs **212** are engaged with the input component and cover plate **214** and are arranged to receive torque from the input and transmit the torque to cover plate **214**. Cover plates **214** and **216** are arranged to transmit torque from springs **212** to the at least one spring **218**, which in turn transmits the torque to the flange and output. As is known in the art, the input component and cover plates **214** and **216** are partially rotatable with respect to each other via springs **212**, and cover plates **214** and **216** are partially rotatable with respect to the flange via the at least one spring **218**.

The at least one spring **212** is located in a respective space **222** formed by curved portion **224** of plate **212**. Portion **224** retains the spring except for in circumferential direction CD into the page. To constrain spring **212** in direction CD, for example, to enable the transfer of torque to spring **212** from the input component, protrusions **226** are formed on plate **214** such that longitudinal ends of the spring are engaged with the protrusions. However, since sufficient room for the input component must be provided in space **222**, the size of the protrusions is limited. As a result, protrusions **226** are only large enough to enable a relatively small portion of the longitudinal ends to engage the protrusions, for example, portions **212A** are free of engagement with the protrusions. Due to this small portion of engagement, compression of spring **212** in direction CD can cause buckling of spring **212** or even cause spring **212** to disengage with the protrusions, both of which adversely affect operation of the vibration damper.

SUMMARY

According to aspects illustrated herein, there is provided a vibration damper, including a first cover plate with an annular portion, and a spring portion located radially outward of the annular portion and including a plurality of spring retaining portions forming respective spaces and a plurality of spring blocking portions including respective protrusion segments

2

and respective tab segments including respective portions of an edge of the first cover plate and having a same first thickness. The damper includes a first plurality of springs at least partially located in the respective spaces, and having respective longitudinal ends with respect to a circumferential line passing through respective longitudinal axes for the plurality of springs. The first plurality of springs is arranged to transmit torque to the first cover plate. The respective protrusion segments have a same second thickness and include respective protrusions extending toward the circumferential line. Respective first portions of the longitudinal ends of the first plurality of springs are engaged with the respective protrusions. Respective second portions of the longitudinal ends of the first plurality of springs are engaged with the respective tab segments.

According to aspects illustrated herein, there is provided a torque converter, including a cover arranged to receive torque and a vibration damper including: a first cover plate including an annular portion and a spring portion located radially outward of the annular portion and including a plurality of spring retaining portions forming respective spaces and a plurality of spring blocking portions including respective protrusion segments and respective tab segments including respective portions of an edge of the first cover plate and having a same first thickness. The damper includes an output and a plurality of springs at least partially located in the respective spaces, and having respective longitudinal ends with respect to a circumferential line passing through respective longitudinal axes for the plurality of springs and connected to the first cover plate. The first cover plate is arranged to transmit torque to the output. The respective protrusion segments have a same second thickness and include respective protrusions extending toward the circumferential line. Respective first portions of the longitudinal ends of the springs are engaged with the respective protrusions. Respective second portions of the longitudinal ends of the springs are engaged with the respective second segments.

According to aspects illustrated herein, there is provided a method of forming a vibration damper, including: stamping a sheet of steel to form a blank for a first cover, the blank including a first portion extending from a center of the disc to a first radial distance from the center and forming first respective portions of an outer circumference for the blank and a plurality of second portions extending to a second radial distance, greater than the first radial distance, from the center and forming second respective portions of the outer circumference; folding the plurality of second portions to overlap the first portion; compressing the plurality of second portions against the first portion to form a plurality of tab segments; curving a radially outermost segment of the first portion to form a plurality of spring blocking portions including the plurality of protrusions and the plurality of tab portions and a circumferentially extending space including a plurality of spring retaining spaces separated by respective spring blocking portions; and forming a plurality of protrusions between respective tab segments and the center of the blank.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments are disclosed, by way of example only, with reference to the accompanying schematic drawings in which corresponding reference symbols indicate corresponding parts, in which:

FIG. 1A is a perspective view of a cylindrical coordinate system demonstrating spatial terminology used in the present application;

3

FIG. 1B is a perspective view of an object in the cylindrical coordinate system of FIG. 1A demonstrating spatial terminology used in the present application; and,

FIG. 2 is a partial cross-sectional view of a torque converter with a vibration damper with a tab spring blocking feature;

FIG. 3 is a front view of the cover plate with the tab spring blocking feature and springs shown in FIG. 2;

FIG. 3A is a detail of area 3A,3B of FIG. 3;

FIG. 3B is a detail of area 3A,3B of FIG. 3 with caps removed from the springs;

FIG. 4A is a cross-sectional view generally along line 4A-4A in FIG. 3 with the spring removed;

FIG. 4B is a cross-sectional view generally along line 4B-4B in FIG. 3 with the spring removed;

FIGS. 5A and 5B illustrate stages in fabrication of the cover plate shown in FIG. 3; and,

FIG. 6 is a partial cross-sectional view of a prior art torque converter and vibration damper.

DETAILED DESCRIPTION

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements of the disclosure. It is to be understood that the disclosure as claimed is not limited to the disclosed aspects.

Furthermore, it is understood that this disclosure is not limited to the particular methodology, materials and modifications described and as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the present disclosure.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this disclosure belongs. It should be understood that any methods, devices or materials similar or equivalent to those described herein can be used in the practice or testing of the disclosure.

FIG. 1A is a perspective view of cylindrical coordinate system **80** demonstrating spatial terminology used in the present application. The present invention is at least partially described within the context of a cylindrical coordinate system. System **80** has a longitudinal axis **81**, used as the reference for the directional and spatial terms that follow. The adjectives “axial,” “radial,” and “circumferential” are with respect to an orientation parallel to axis **81**, radius **82** (which is orthogonal to axis **81**), and circumference **83**, respectively. The adjectives “axial,” “radial” and “circumferential” also are regarding orientation parallel to respective planes. To clarify the disposition of the various planes, objects **84**, **85**, and **86** are used. Surface **87** of object **84** forms an axial plane. That is, axis **81** forms a line along the surface. Surface **88** of object **85** forms a radial plane. That is, radius **82** forms a line along the surface. Surface **89** of object **86** forms a circumferential plane. That is, circumference **83** forms a line along the surface. As a further example, axial movement or disposition is parallel to axis **81**, radial movement or disposition is parallel to radius **82**, and circumferential movement or disposition is parallel to circumference **83**. Rotation is with respect to axis **81**.

The adverbs “axially,” “radially,” and “circumferentially” are with respect to an orientation parallel to axis **81**, radius **82**, or circumference **83**, respectively. The adverbs “axially,” “radially,” and “circumferentially” also are regarding orientation parallel to respective planes.

FIG. 1B is a perspective view of object **90** in cylindrical coordinate system **80** of FIG. 1A demonstrating spatial ter-

4

minology used in the present application. Cylindrical object **90** is representative of a cylindrical object in a cylindrical coordinate system and is not intended to limit the present invention in any manner. Object **90** includes axial surface **91**, radial surface **92**, and circumferential surface **93**. Surface **91** is part of an axial plane, surface **92** is part of a radial plane, and surface **93** is a circumferential surface.

FIG. 2 is a partial cross-sectional view of torque converter **100** with vibration damper **102** with a tab spring blocking feature. Torque converter **100** includes cover **104**, arranged to receive torque, and pump shell **108**, for pump **110**, fixedly secured to the cover. By fixedly secured we mean that no relative motion is possible between the cover and the pump shell. The torque converter also includes turbine **112** hydraulically coupled to the pump, turbine shell **114**, stator **116**, and output **118** arranged to transmit torque from the torque converter.

Vibration damper **102** includes input component **122**, plurality of springs **124**, and cover plate **126**. In an example embodiment, the damper includes cover plate **128** fixedly secured to cover plate **126**, at least one spring **130**, and flange **132** forming output **118**. The at least one spring **130** is engaged with cover plates **126** and **128** and the flange. Springs **124** are engaged with the input component and cover plate **126** and are arranged to receive torque from the input component and transmit the torque to cover plate **126**. Cover plates **126** and **128** are arranged to transmit torque from springs **124** to the at least one spring **130**, which in turn transmits the torque to the flange and output. As is known in the art, the input component and cover plates **126** and **128** are partially rotatable with respect to each other via springs **124**, and cover plates **126** and **128** are partially rotatable with respect to the flange via the at least one spring **130**.

In an example embodiment, the torque converter includes torque converter clutch **133** and the input component is connected to the clutch. The clutch is controllable to connect and disconnect the cover to and from the vibration damper.

FIG. 3 is a front view of cover plate **126** with the tab spring blocking feature and springs **124** shown in FIG. 2. FIG. 3A is a detail area 3A,3B of FIG. 3. FIG. 3B is a detail of area 3A,3B of FIG. 3 with cap **152** removed from springs **124**. Respective portions LE-1 of longitudinal ends LE of springs **124** are engaged with respective protrusions **148** and respective portions LE-2 of longitudinal ends LE of springs **124** are engaged with respective tab segments **146**. As seen in FIG. 3A, ends LE-1 and LE-2 are engaged with protrusions **148** and tab segments **146**, respectively, via portions **152A** and **152B** of caps **152**, respectively. As seen in FIG. 3B, portions LE-1 and LE-2 are in direct contact with protrusions **148** and tab segments **146**, respectively.

FIG. 4A is a cross-sectional view generally along line 4A-4A in FIG. 3 with the spring removed.

FIG. 4B is a cross-sectional view generally along line 4B-4B in FIG. 3 with the spring removed. The following should be viewed in light of FIGS. 2 through 4B. Cover plate **126** includes annular portion **134** and spring portion **136**, located radially outward of the annular portion. The spring portion includes a plurality of spring retaining portions **138** forming respective spaces **140**, as seen in FIG. 4A, and a plurality of spring blocking portions **142** with spaces **143**, as seen in FIG. 4B. Each portion **142** includes protrusion segment **144** and tab segment **146**. Segments **146** include respective portions EP of edge E of cover plate **126** and having a same thickness T1. Springs **124** are located in spaces **140** and have longitudinal ends LE with respect to circumferential line CL passing through respective longitudinal axes LA for springs **124**.

5

Protrusion segments **144** have a same thickness **T2**, equal to about one half of **T1** and include respective protrusions **148** extending toward **CL**. The longitudinal ends of springs **124** are engaged with the protrusions and the tab segments. The tab segments include outer portions **OP** having thickness **T2** and continuous with the protrusions, and inner portions **IP**, radially inward of **OP** with respect to **CL** and also having thickness **T2**. The tab segments include curved portions **CP**, including portions **EP**, joining respective **OPs** and **IPs**. For example, the tab segment is formed by folded over portions of the material forming plate **126**.

In an example embodiment, springs **124** include caps **152** at each longitudinal end and the caps are in contact with the protrusions and the tab segments.

FIGS. 5A and **5B** illustrate stages in fabrication of cover plate **126** shown in **FIG. 3**. The following should be viewed in light of **FIGS. 2** through **5B**. The following describes an example method of forming a vibration damper. As shown in **FIG. 5A**, a step stamps a sheet, for example, of steel, to form blank **153** for cover **126** for a vibration damper. The blank includes portion **154** extending from center **C** of the disc as far as radial distance **RD1** from the center, forming portions **P1** of outer circumference **OC** for the blank. The blank includes portions **156** extending as far as radial distance **RD2**, greater than radial distance **RD1**, from the center and forming portions **P2** of the outer circumference. Another step, as shown in **FIG. 5B**, folds portions **156** to overlap portion **154**. A further step compresses portions **156** against portion **154** to form tab segments, such as segments **146** shown in **FIG. 4B**. A step forms protrusions **148** between respective tab portions and the center of the blank. Another step curves radially outermost segment **158** of the blank to form spring blocking portions including protrusions **148** and tab portions **146** and circumferentially extending space **160** including spring retaining spaces **140** separated by respective spring blocking portions. A further step inserts springs **122** in the spring retaining spaces such that respective ends of the springs engage protrusions **148** and tab portions **146**. A still further step rolls the outer circumference of the blank to trap springs **122** in the spring retaining spaces.

In an example embodiment, forming the tab portions includes forming the entire outer circumference of the blank at radial distance **RD1**. In an example embodiment, rolling the outer circumference of the blank includes forming a largest extent **162**, between the outer circumference and portion **154** in a direction orthogonal to the outer circumference, for openings **164** for spring retaining spaces **140** to be more than diameter **D** of springs **122** to enable the springs to be inserted in spaces **140**.

Advantageously, tab portions **146** increase the area of ends **LE** for springs **122** engaged with cover plate **126**. This increased area reduces the likelihood of springs **122** buckling or popping out of spaces **140** when springs **122** are compressed. Further, the increase in engagement area for springs **122** is accomplished by modifying a part already used cover plate **126** by performing additional stamping and forming operations. Thus, a single plate **126** retains springs **122** via portions **166**, axially restrains the springs via spring blocking portions **142**, and increases the engagement area of the springs with the cover plate via tab segments **146**, all without the use of additional components.

It will be appreciated that various of the above-disclosed and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations, or improvements

6

therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

What is claimed is:

1. A vibration damper, comprising:
 - a first cover plate including:
 - an annular portion; and,
 - a spring portion located radially outward of the annular portion and including:
 - a plurality of spring retaining portions forming respective spaces; and,
 - a plurality of spring blocking portions including:
 - respective protrusion segments; and,
 - respective tab segments including:
 - respective end portions forming respective distal ends of the respective tab segments and having a first thickness; and,
 - respective portions of an edge of the first cover plate, the respective portions of the edge having a same second thickness, substantially equal to one half the first thickness; and,
 - a first plurality of springs at least partially located in the respective spaces, and having respective longitudinal ends with respect to a circumferential line passing through respective longitudinal axes for the plurality of springs, wherein:
 - the first plurality of springs is arranged to transmit torque to the first cover plate;
 - the respective protrusion segments have the same second thickness and include respective protrusions extending toward the circumferential line;
 - respective first portions of the longitudinal ends of the first plurality of springs are in contact with the respective protrusions; and,
 - respective second portions of the longitudinal ends of the first plurality of springs are in contact with the respective tab segments.
2. The vibration damper of claim 1, wherein the respective tab segments include:
 - respective outer portions, having the second thickness, continuous with the respective protrusions;
 - respective inner portions, radially inward of the outer portion with respect to the circumferential line, having the second thickness; and,
 - respective curved portions, including the respective portions of the edge, joining the respective inner and outer portions.
3. The vibration damper of claim 1, further comprising:
 - an output flange; and,
 - a second plurality of springs engaged with first cover plate and the output flange.
4. The vibration damper of claim 1, further comprising:
 - an input element engaged with the first plurality of springs and arranged to receive torque from a cover for a torque converter;
 - an output flange; and,
 - a second plurality of springs engaged with the first cover plate and the output flange.
5. A torque converter, comprising:
 - a cover arranged to receive torque; and,
 - a vibration damper including:
 - a cover plate including:
 - an annular portion; and,
 - a spring portion located radially outward of the annular portion and including:
 - a plurality of spring retaining portions forming respective spaces; and,

7

a plurality of spring blocking portions including:
 respective protrusion segments; and,
 respective tab segments including:
 respective end portions forming respective distal
 ends of the respective tab segments and having a
 first thickness; and,
 respective portions of an edge of the cover plat,
 the respective portions of the edge having a same
 second thickness substantially equal to one half
 the first thickness;

a plurality of springs at least partially located in the
 respective spaces, and having respective longitudinal
 ends with respect to a circumferential line passing
 through respective longitudinal axes for the plurality
 of springs;

a plurality of caps, each cap located at a respective
 longitudinal end; and,
 an output, wherein:
 the cover plate is arranged to transmit torque to the
 output;
 the respective protrusion segments have the same sec-
 ond thickness and include respective protrusions
 extending toward the circumferential line;
 a respective first portion of said each cap is in contact
 with a respective protrusion; and,
 a respective second portion of said each cap is in
 contact with a respective tab segment.

6. The torque converter of claim 5, wherein the respective
 tab segments include:
 respective outer portions, having the second thickness,
 continuous with the respective protrusions;
 respective inner portions, radially inward of the outer por-
 tion with respect to the circumferential line, having the
 second thickness; and,
 respective curved portions, including the respective por-
 tions of the edge, joining the respective inner and outer
 portions.

7. The torque converter of claim 5, wherein:
 the output includes a flange; and,
 the vibration damper includes:
 an input element engaged with the cover and the first
 plurality of springs; and,
 a second plurality of springs engaged with the cover and
 the flange.

8

8. A vibration damper, comprising:
 a first cover plate including:
 an annular portion; and,
 a spring portion located radially outward of the annular
 portion and including:
 a plurality of spring retaining portions forming
 respective spaces; and,
 a plurality of spring blocking portions including:
 respective protrusion segments; and,
 respective tab segments including:
 respective end portions forming respective distal
 ends of the respective tab segments and having a
 first thickness; and,
 respective portions of an edge of the first cover
 plate, the respective portions of the edge having
 a same second thickness substantially equal to
 one half the first thickness; and,
 a first plurality of springs at least partially located in the
 respective spaces, and having respective longitudinal
 ends with respect to a circumferential line passing
 through respective longitudinal axes for the plurality of
 springs, wherein:
 the first plurality of springs is arranged to transmit
 torque to the first cover plate;
 the respective protrusion segments have the same sec-
 ond thickness and include respective protrusions
 extending toward the circumferential line; and,
 wherein:
 respective first portions of the longitudinal ends of the
 first plurality of springs are in contact with the respec-
 tive protrusions; and,
 respective second portions of the longitudinal ends of
 the first plurality of springs are in contact with the
 respective tab segments; or,
 wherein:
 the damper includes a plurality of caps, each cap located
 at a respective longitudinal end;
 a respective first portion of said each cap is in contact
 with a respective protrusion; and,
 a respective second portion of said each cap is in contact
 with a respective tab segment.

* * * * *