



US009243702B2

(12) **United States Patent**
Resh et al.

(10) **Patent No.:** **US 9,243,702 B2**
(45) **Date of Patent:** **Jan. 26, 2016**

(54) **TORQUE CONVERTER BLADE TAB UNDERCUTS**

(75) Inventors: **Michael L. Resh**, Massillon, OH (US);
Randy L. Keller, Polk, OH (US)

(73) Assignee: **Schaeffler Technologies AG & Co. KG**,
Herzogenaurach (DE)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 819 days.

(21) Appl. No.: **13/548,987**

(22) Filed: **Jul. 13, 2012**

(65) **Prior Publication Data**

US 2013/0022470 A1 Jan. 24, 2013

Related U.S. Application Data

(60) Provisional application No. 61/508,810, filed on Jul.
18, 2011.

(51) **Int. Cl.**
F16H 41/24 (2006.01)
F16H 41/28 (2006.01)

(52) **U.S. Cl.**
CPC **F16H 41/28** (2013.01); **Y10T 29/49236**
(2015.01)

(58) **Field of Classification Search**
CPC F16H 41/28
USPC 60/367, 330, 338
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,311,958	A *	2/1943	Neracher et al.	60/367
2,890,661	A *	6/1959	Egbert	416/180
8,434,300	B2 *	5/2013	Marathe	60/366
2007/0258820	A1	11/2007	Uhler et al.	
2009/0241533	A1	10/2009	Marathe	

* cited by examiner

Primary Examiner — Dwayne J White


Assistant Examiner — Jason Fountain

(74) *Attorney, Agent, or Firm* — Simpson & Simpson, PLLC

(57) **ABSTRACT**

A blade for a torque converter, including: a body with first and second blade side surfaces and a blade edge surface connecting the first and second blade side surfaces; and a tab extending from the blade edge surface and arranged for insertion through an opening in a core ring for the torque converter. The tab includes: a distal end furthest from the blade edge surface; first and second tab edge surfaces in communication with the distal end; and first and second indentations in the first and second tab edge surfaces, respectively, between the distal end and the blade edge surface. The core ring forms at least respective portions of respective inner circumferences for a turbine and pump for the torque converter. After insertion through the opening, the tab is arranged to be bent along a line connecting the indentations so that a portion of the tab engages the core ring.

15 Claims, 5 Drawing Sheets






Fig. 1A




Fig. 1B






Fig. 2






Fig. 5A




Fig. 5B




Fig. 6

1

TORQUE CONVERTER BLADE TAB UNDERCUTS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit under 35 U.S.C. §119 (e) of U.S. Provisional Patent Application No. 61/508,810 filed Jul. 18, 2011 which application is incorporated herein by reference.

TECHNICAL FIELD

The present disclosure relates to a blade for a torque converter requiring less force for connection to a core ring for the torque converter. Specifically, the disclosure relates to a blade with undercuts at a tab to reduce the force needed to bend the tab to secure the blade to the core ring.

BACKGROUND

It is known to insert solid tabs for blades through a core ring for a torque converter and to bend the tabs to secure the blades to the core ring. Bending the solid tabs can require a significant amount of force, which can cause the blade to be displaced, changing blade angles and affecting characteristics of the torque converter dependent upon blade configuration.

SUMMARY

According to aspects illustrated herein, there is provided a blade for a torque converter, including: a body with first and second blade side surfaces and a blade edge surface connecting the first and second blade side surfaces; and a first tab extending from the blade edge surface and arranged for insertion through an opening in a core ring for the torque converter. The first tab includes: a distal end furthest from the blade edge surface; first and second tab edge surfaces in communication with the distal end; and first and second indentations in the first and second tab edge surfaces, respectively, between the distal end and the blade edge surface. The core ring forms at least respective portions of respective inner circumferences for a turbine and pump for the torque converter. After insertion through the opening, the first tab is arranged to be bent along a line connecting the first and second indentations so that a portion of the first tab engages the core ring.

According to aspects illustrated herein, there is provided a torque converter, including: a turbine with a turbine shell; a pump with a pump shell; a core ring with an opening passing through the core ring; and a blade including: a body with a blade edge surface; at least one first tab extending from the blade edge surface and connected to the pump shell or the turbine shell; and a second tab extending from the blade edge surface and partially disposed within the opening in the core ring. The second tab includes: a distal end; first and second tab edge surfaces converging at the distal end; and first and second indentations in the first and second tab edge surfaces, respectively, between the distal end and the blade edge surface. The second tab is bent along a line connecting the first and second indentations so that a portion of the second tab engages the core ring.

According to aspects illustrated herein, there is provided a method of forming a blade for a torque converter, including: forming a body with first and second blade side surfaces and a blade edge surface connecting the first and second blade side surfaces; forming a first tab extending from the blade edge surface and including a distal end furthest from the blade

2

edge surface; forming, on the first tab, first and second tab edge surfaces in communication with the distal end; and forming first and second indentations in the first and second tab edge surfaces, respectively, between the distal end and the blade edge surface. The first tab is arranged for insertion through an opening in a core ring for the torque converter. The core ring forms at least respective portions of respective inner circumferences for a turbine and pump for the torque converter. After insertion through the opening, the first tab is arranged to be bent along a line connecting the first and second indentations so that a portion of the first tab engages the core ring.

According to aspects illustrated herein, there is provided a method of assembling a torque converter including: a turbine with a turbine shell; a pump with a pump shell; and a core ring disposing between the turbine shell and the pump shell and including an opening passing through the core ring. The method includes: forming a body of a blade with a blade edge surface; forming at least one first tab extending from the blade edge surface; forming a second tab extending from the blade edge surface. The second tab includes: a distal end; first and second tab edge surfaces connected to the blade edge surface at first and second connecting areas, respectively, and in communication with the distal end; and first and second indentations in the first and second tab edge surfaces, respectively, between the distal end and the first and second connecting areas, respectively. The method includes: connecting the at least one first tab to the pump shell or the turbine shell; partially disposing the second tab in the opening; and bending the second tab along a line connecting the first and second indentations so that a portion of the second tab engages the core ring.

These and other objects and advantages of the present disclosure will be readily appreciable from the following description of the invention and from the accompanying drawings and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments are disclosed, by way of example only, with reference to the accompanying schematic drawings in which corresponding reference symbols indicate corresponding parts, in which:

FIG. 1A is a perspective view of a cylindrical coordinate system demonstrating spatial terminology used in the present application;

FIG. 1B is a perspective view of an object in the cylindrical coordinate system of FIG. 1A demonstrating spatial terminology used in the present application; and,

FIG. 2 is a perspective view of a blade with tab undercuts; FIG. 3 is an alternate perspective view of the blade shown in FIG. 2;

FIG. 4 is a detail of area 4 in FIG. 2;

FIGS. 5A and 5B are details of exemplary embodiments of a tab with undercuts; and,

FIG. 6 is a partial cross-sectional view of a torque converter with a blade with tab undercuts.

DETAILED DESCRIPTION

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements of the disclosure. It is to be understood that the disclosure as claimed is not limited to the disclosed aspects.

Furthermore, it is understood that this disclosure is not limited to the particular methodology, materials and modifi-

3

cations described and as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the present disclosure.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this disclosure belongs. It should be understood that any methods, devices or materials similar or equivalent to those described herein can be used in the practice or testing of the disclosure.

FIG. 1A is a perspective view of cylindrical coordinate system **80** demonstrating spatial terminology used in the present application. The present invention is at least partially described within the context of a cylindrical coordinate system. System **80** has a longitudinal axis **81**, used as the reference for the directional and spatial terms that follow. The adjectives “axial,” “radial,” and “circumferential” are with respect to an orientation parallel to axis **81**, radius **82** (which is orthogonal to axis **81**), and circumference **83**, respectively. The adjectives “axial,” “radial” and “circumferential” also are regarding orientation parallel to respective planes. To clarify the disposition of the various planes, objects **84**, **85**, and **86** are used. Surface **87** of object **84** forms an axial plane. That is, axis **81** forms a line along the surface. Surface **88** of object **85** forms a radial plane. That is, radius **82** forms a line along the surface. Surface **89** of object **86** forms a circumferential plane. That is, circumference **83** forms a line along the surface. As a further example, axial movement or disposition is parallel to axis **81**, radial movement or disposition is parallel to radius **82**, and circumferential movement or disposition is parallel to circumference **83**. Rotation is with respect to axis **81**.

The adverbs “axially,” “radially,” and “circumferentially” are with respect to an orientation parallel to axis **81**, radius **82**, or circumference **83**, respectively. The adverbs “axially,” “radially,” and “circumferentially” also are regarding orientation parallel to respective planes.

FIG. 1B is a perspective view of object **90** in cylindrical coordinate system **80** of FIG. 1A demonstrating spatial terminology used in the present application. Cylindrical object **90** is representative of a cylindrical object in a cylindrical coordinate system and is not intended to limit the present invention in any manner. Object **90** includes axial surface **91**, radial surface **92**, and circumferential surface **93**. Surface **91** is part of an axial plane, surface **92** is part of a radial plane, and surface **93** is a circumferential surface.

FIG. 2 is a perspective view of blade **100** with tab undercuts.

FIG. 3 is an alternate perspective view of blade **100** shown in FIG. 2.

FIG. 4 is a detail of the tab with undercuts shown in FIG. 2. The following should be viewed in light of FIGS. 2 through 4. Blade **100** for a torque converter includes body **102** with blade side surfaces **104** and **106** and blade edge surface **108** connecting the blade side surfaces. The blade includes tab **110** extending from blade edge surface **108** and arranged for insertion through an opening in a core ring for the torque converter as further described below. Tab **110** includes distal end **112** furthest from blade edge surface **108** and tab edge surfaces **114** and **116** in communication with the distal end. In an example embodiment, tab edge surfaces **114** and **116** converge at the distal end. Indentations **118** and **120** are located in the tab edge surfaces **114** and **116**, respectively, between the distal end and blade edge surface **108**.

The core ring forms at least respective portions of respective inner circumferences for a turbine and pump for the torque converter, and after insertion through the opening, tab

4

110 is arranged to be bent along line **122** connecting indentations **118** and **120** so that portion **124** of the tab **110** engages the core ring.

In an example embodiment, tab edge surfaces **114** and **116** are connected to blade edge surface **108** at connecting areas **126** and **128**, respectively, and indentations **118** and **120** are located between the distal end and connecting areas **126** and **128**, respectively. In an example embodiment, tab edge surface **114** includes portion **114A** between indentation **118** and connection area **126**, and portion **114B** between the distal end and indentation **118**. In an example embodiment, portions **114A** and **114B** are aligned. For example, the respective surfaces forming portions **114A** and **114B** are co-planar. In an example embodiment, tab edge surface **116** includes portion **116A** between indentation **120** and connection area **128**, and portion **116B** between the distal end and indentation **120**. In an example embodiment, portions **116A** and **116B** are aligned. For example, the respective surfaces forming portions **116A** and **116B** are co-planar.

In an example embodiment, tab **110** includes tab side surfaces **130** and **132** continuous with blade side surfaces **104** and **106**, respectively, and one of tab side surfaces **130** or **132** is arranged to engage the core ring.

In an example embodiment, body **102** includes at least one tab **134** extending from blade edge surface **108** and arranged to engage a turbine shell or a pump shell for the turbine or the pump, respectively, as further described below.

FIGS. 5A and 5B are respective details of exemplary embodiments of a tab with undercuts. In FIG. 5A, portions **114C** and **116C** of edges **114** and **116**, respectively, are substantially parallel. In FIG. 5B, portions **114A** and **114D** and portions **116A** and **116D** of edges **114** and **116**, respectively, are not aligned.

FIG. 6 is a partial cross-sectional view of torque converter **200** with blade **100** with tab undercuts. The following should be viewed in light of FIGS. 2 through 6. Torque converter **200** includes pump **202**, turbine **204**, and stator **206**. Stator **206** is for multiplying torque as is commonly known in the art. Pump **202** includes pump shell **208** and turbine **204** includes turbine shell **210**. Converter **200** also includes core ring **212** with openings **214**. The core ring forms at least a portion of the respective inner circumferences for the pump and turbine. It is understood that the pump and turbine includes respective pluralities of blades. In FIG. 5, blades **100** are installed in both the pump and the turbine. However, it should be understood that blades **100** could be installed in only one of the pump or the turbine. Due to the location of the cross-section line for FIG. 5, tabs **110** and **134** are not visible for blade **100** in the turbine. Tabs **110** extend through openings **214** and are bent over such that portion **124** of the tab contacts inner surface **216** of the core ring. Tabs **134** are used to connect the blades to the pump shell and the turbine shell.

Although blade **100** has been shown with a particular shape and configuration, for example, position of tabs **110** and **134**, it should be understood blade **100** is not limited to the particular shape and configuration shown and that other shapes and configurations are possible. For example, tab **110** could be located on a different portion of section **108A** of the blade edge surface, tab **100** could have different proportions, or tabs **134** could vary in number, shape, or location. Although torque converter **200** has been shown with a particular configuration and set of components, it should be understood that torque converter **200** is not limited to the particular configuration and set of components shown and that other configurations and sets of components are possible. In general, blade **100** can be used with any hydraulic torque transfer device having a turbine and/or a pump.

5

It will be appreciated that various of the above-disclosed and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations, or improvements

What we claim is:

1. A blade for a torque converter, comprising:

a body with first and second blade side surfaces and a blade edge surface connecting the first and second blade side surfaces; and,

a first tab extending from the blade edge surface and arranged for insertion through an opening in a core ring for the torque converter, the first tab including:

a distal end furthest from the blade edge surface;

first and second tab edge surfaces in communication with the distal end; and,

first and second indentations in the first and second tab edge surfaces, respectively, between the distal end and the blade edge surface, wherein:

the first and second indentations are separated from the blade edge surface by respective portions of the first and second tab edge surfaces;

the core ring forms at least respective portions of respective inner circumferences for a turbine and pump for the torque converter; and,

after insertion through the opening, the first tab is arranged to be bent along a line connecting the first and second indentations so that a portion of the first tab engages the core ring.

2. The blade of claim 1, wherein:

the first and second tab edge surfaces are connected to the blade edge surface at first and second connecting areas, respectively; and,

the first and second indentations are located between the distal end and the first and second connecting areas, respectively.

3. The blade of claim 2, wherein:

the first tab edge surface includes a first portion between the first indentation and the first connection area, and a second portion between the distal end and the first indentation; and,

the first and second portions are aligned.

4. The blade of claim 2, wherein:

the second tab edge surface includes a first portion between the second indentation and the second connection area, and a second portion between the distal end and the second indentation; and,

the first and second portions are aligned.

5. The blade of claim 1, wherein:

the first tab includes first and second tab side surfaces continuous with the first and second blade side surfaces, respectively; and,

the first or second tab side surface is arranged to engage the core ring.

6. The blade of claim 1, wherein the body includes at least one second tab extending from the blade edge surface and arranged to engage a turbine shell or a pump shell for the turbine or the pump, respectively.

7. A torque converter, comprising:

a turbine with a turbine shell;

a pump with a pump shell;

a core ring with an opening passing through the core ring; and,

6

a blade including:

a body with a blade edge surface;

at least one first tab extending from the blade edge surface and connected to the pump shell or the turbine shell; and,

a second tab extending from the blade edge surface and partially disposed within the opening in the core ring, the second tab including:

a distal end;

first and second tab edge surfaces in communication with the distal end; and,

first and second indentations in the first and second tab edge surfaces, respectively, between the distal end and the blade edge surface, wherein:

the second tab is bent along a line connecting the first and second indentations so that a portion of the second tab engages the core ring; and,

the first and second indentations are separated from the blade edge surface by respective portions of the first and second tab edge surfaces.

8. The torque converter of claim 7, wherein:

the first and second tab edge surfaces are connected to the blade edge surface at first and second connecting areas, respectively; and,

the first and second indentations are located between the distal end and the first and second connecting areas, respectively.

9. The torque converter of claim 8, wherein:

the first tab edge surface includes a first portion between the first indentation and the first connection area, and a second portion between the distal end and the first indentation; and,

the first and second portions are aligned.

10. The torque converter of claim 8, wherein:

the second tab edge surface includes a first portion between the second indentation and the second connection area, and a second portion between the distal end and the second indentation; and,

the first and second portions are aligned.

11. The torque converter of claim 7, wherein:

the blade includes first and second blade side surfaces connected by the blade edge surface;

the second tab includes first and second tab side surfaces continuous with the first and second blade side surfaces, respectively; and,

the first or second tab side surface engages the core ring.

12. A method of assembling a torque converter including:

a turbine with a turbine shell; a pump with a pump shell; and a core ring disposing between the turbine shell and the pump shell and including an opening passing through the core ring, the method comprising:

forming a body of a blade with a blade edge surface;

forming at least one first tab extending from the blade edge surface;

forming a second tab extending from the blade edge surface and including:

a distal end;

first and second tab edge surfaces connected to the blade edge surface at first and second connecting areas, respectively, and in communication with the distal end; and,

first and second indentations in the first and second tab edge surfaces, respectively, between the distal end and the first and second connecting areas, respectively, the first and second indentations separated from the blade edge surface by respective portions of the first and second tab edge surfaces;

connecting the at least one first tab to the pump shell or the turbine shell;
 partially disposing the second tab in the opening; and,
 bending the second tab along a line connecting the first and second indentations so that a portion of the second tab 5
 engages the core ring.

13. The method of claim **12**, wherein:

forming the body of the blade includes forming first and second blade side surfaces connected by the blade edge surface; 10

forming the second tab includes forming first and second tab side surfaces continuous with the first and second blade side surfaces, respectively; and,

bending the second tab includes bending the second tab such that the first or second tab side surface engages the 15
 core ring.

14. The method of claim **12**, wherein forming the first tab edge surface includes:

forming a first portion between the first indentation and the first connection area, and a second portion between the 20
 distal end and the first indentation; and,
 aligning the first and second portions.

15. The method of claim **12**, wherein forming the second tab edge surface includes:

forming a first portion between the second indentation and 25
 the second connection area, and a second portion
 between the distal end and the second indentation; and,
 aligning the first and second portions.

* * * * *