



US009416825B2

(12) **United States Patent**  
**Lee**

(10) **Patent No.:** **US 9,416,825 B2**  
(45) **Date of Patent:** **Aug. 16, 2016**

(54) **ALL-WHEEL DRIVE DISCONNECT CLUTCH**

2011/006 (2013.01); F16D 2023/0643  
(2013.01); F16H 48/11 (2013.01)

(71) Applicant: **Schaeffler Technologies AG & Co. KG**,  
Herzogenaurach (DE)

(58) **Field of Classification Search**  
CPC ..... F16D 13/38; F16D 23/0612; F16D  
2023/0643; F16D 2011/006; F16D 13/06;  
F16D 13/14; F16D 43/211  
See application file for complete search history.

(72) Inventor: **Brian Lee**, York, SC (US)

(73) Assignee: **Schaeffler Technologies AG & Co. KG**,  
Herzogenaurach (DE)

(56) **References Cited**

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

(21) Appl. No.: **14/620,876**

1,156,848 A 10/1915 Miller  
3,913,713 A 10/1975 F'Geppert  
4,138,006 A 2/1979 Benson, Jr.

(22) Filed: **Feb. 12, 2015**

(Continued)

(65) **Prior Publication Data**

US 2015/0152921 A1 Jun. 4, 2015

FOREIGN PATENT DOCUMENTS

**Related U.S. Application Data**

CN 1656327 8/2005  
CN 101344162 1/2009  
JP 2001099186 4/2001

(63) Continuation-in-part of application No. 13/849,142,  
filed on Mar. 22, 2013, now abandoned.

Primary Examiner — Jacob S Scott

Assistant Examiner — Tinh Dang

(60) Provisional application No. 61/615,655, filed on Mar.  
26, 2012.

(74) *Attorney, Agent, or Firm* — Simpson & Simpson, PLLC

(51) **Int. Cl.**

**F16D 13/14** (2006.01)  
**F16D 15/00** (2006.01)  
**F16D 23/06** (2006.01)  
**F16D 13/06** (2006.01)  
**F16D 13/52** (2006.01)  
**F16D 43/21** (2006.01)  
**B60K 17/02** (2006.01)

(57) **ABSTRACT**



A drive disconnect clutch assembly, including: an input com-  
ponent arranged to receive torque from a motor; an output  
gear; and a clutch including: a flexible piston plate; at least  
one clutch plate; at least one wedge plate; and friction mater-  
ial disposed between the at least one clutch plate and the at  
least one wedge plate. For a synchronizing mode, the flexible  
piston plate is arranged to displace in an axial direction to  
engage the at least one clutch plate with the at least one wedge  
plate to enable transfer of torque from the input component to  
the output gear. For a locked mode, a first portion of the  
flexible piston plate is arranged to further displace in the first  
axial direction to expand the at least one wedge plate radially  
outward and non-rotatably connect the at least one wedge  
plate, the input component, and the output gear.

(Continued)

(52) **U.S. Cl.**

CPC ..... **F16D 13/06** (2013.01); **F16D 13/14**  
(2013.01); **F16D 13/52** (2013.01); **F16D 15/00**  
(2013.01); **F16D 23/0612** (2013.01); **F16D**  
**43/211** (2013.01); **B60K 17/02** (2013.01); **F16D**

**20 Claims, 8 Drawing Sheets**








Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5










Fig. 8

**ALL-WHEEL DRIVE DISCONNECT CLUTCH****CROSS-REFERENCE TO RELATED APPLICATIONS**

This is a continuation-in-part patent application under 35 U.S.C. §120 of U.S. patent application Ser. No. 13/849,142, filed Mar. 22, 2013, which application claims the benefit under 35 U.S.C. 119(e) of U.S. Provisional Application No. 61/615,655 filed Mar. 26, 2012, which applications are incorporated herein by reference in their entirety.

**TECHNICAL FIELD**

The present disclosure relates a drive disconnect clutch for providing torque to a secondary drive shaft in an all-wheel drive vehicle, specifically, a drive disconnect clutch providing synchronization with frictional engagement of clutch plates and a locked connection with expanding wedge plates.

**BACKGROUND**

For providing torque to a secondary drive shaft of an all-wheel drive vehicle, U.S. Pat. No. 7,150,694 is an example of using a clutch in a power transfer unit (PTU), which adds to the mass and size of the PTU. U.S. Pat. No. 7,150,694 and U.S. Pat. No. 7,309,301 are examples of using a transfer (typically wet) clutch in a differential to control torque to a secondary drive shaft. Pressurized fluid must be continuously supplied to keep the clutches in a closed mode, adding to the power usage associated with usage of the clutches. U.S. Pat. No. 6,520,885 is an example of using a roller or dog clutch to control torque to a secondary drive shaft. However, a vehicle must be at a stand still to use of such clutches.

**SUMMARY**

According to aspects illustrated herein, there is provided a drive disconnect clutch assembly, including: an input component arranged to receive torque from a motor; an output gear; and a clutch including: a flexible piston plate; at least one clutch plate; at least one wedge plate; and respective friction material disposed between the at least one clutch plate and the at least one wedge plate. For a synchronizing mode, the flexible piston plate is arranged to displace in a first axial direction to engage the at least one clutch plate with the at least one wedge plate to enable transfer of torque from the input component to the output gear. For a locked mode, a first portion of the flexible piston plate is arranged to further displace in the first axial direction to expand the at least one wedge plate radially outward and non-rotatably connect the at least one wedge plate, the input component, and the output gear.

According to aspects illustrated herein, there is provided a drive disconnect clutch, including: an input component arranged for driving connection to a motor; an output gear; and a clutch including: a flexible piston plate; at least one clutch plate; at least one wedge plate; and respective friction material disposed between the at least one clutch plate and the at least one wedge plate. For a synchronizing mode, the flexible piston plate is arranged to displace a distance in a first axial direction to engage the at least one clutch plate with the at least one wedge plate to enable transfer of torque from the input component to the output gear. For a locked mode a first portion of the flexible piston plate is arranged to further displace in the first axial direction to displace: the at least one wedge plate to non-rotatably connect the input component

and the output gear via contact of the at least one wedge plate with the input component and the output gear; and a second portion of the flexible piston plate radially outward.

According to aspects illustrated herein, there is provided a drive disconnect clutch, including: an input component arranged to receive torque from a motor; an output gear; and a clutch including: a piston plate; at least one clutch plate; at least one wedge plate; and respective friction material disposed between the at least one clutch plate and the at least one wedge plate. For a synchronizing mode, the flexible piston plate is arranged to displace a first distance in a first axial distance to clamp the at least one clutch plate and the at least one wedge plate to rotationally connect the input component and the output gear. For a locked mode: a first portion of the flexible piston plate is arranged to further displace in the first axial direction to displace the at least one wedge plate to lock respective rotations of the input component and the output gear via contact of the at least one wedge plate with the input component and the output gear; and a second portion of the flexible piston plate is arranged to displace radially outward as the first portion of the flexible piston plate further displaces in the first axial direction.

**BRIEF DESCRIPTION OF THE DRAWINGS**

Various embodiments are disclosed, by way of example only, with reference to the accompanying schematic drawings in which corresponding reference symbols indicate corresponding parts, in which:

FIG. 1 is a perspective view of a cylindrical coordinate system demonstrating spatial terminology used in the present application; and,

FIG. 2 is a schematic representation of a vehicle with a drive disconnect clutch assembly in a differential assembly;

FIG. 3 is a cross-sectional view of a drive disconnect clutch assembly in a differential assembly;

FIG. 4 is a detail of the drive disconnect clutch assembly in FIG. 3 in a disengaged mode;

FIG. 5 is a detail of the drive disconnect clutch assembly in FIG. 3 in a synchronizing mode;

FIG. 6 is a sectional view generally along line 6-6 in FIG. 5;

FIG. 7 is a detail of the drive disconnect clutch assembly in FIG. 3 in a locked mode; and,

FIG. 8 is a sectional view generally along line 8-8 in FIG. 7.

**DETAILED DESCRIPTION**

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements of the disclosure. It is to be understood that the disclosure as claimed is not limited to the disclosed aspects.

Furthermore, it is understood that this disclosure is not limited to the particular methodology, materials and modifications described and as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the present disclosure.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this disclosure belongs. It should be understood that any methods, devices or materials similar or equivalent to those described herein can be used in the practice or testing of the disclosure.

3

FIG. 1 is a perspective view of cylindrical coordinate system **10** demonstrating spatial terminology used in the present application. The present application is at least partially described within the context of a cylindrical coordinate system. System **10** includes longitudinal axis **11**, used as the reference for the directional and spatial terms that follow. Axial direction AD is parallel to axis **11**. Radial direction RD is orthogonal to axis **11**. Circumferential direction CD is defined by an endpoint of radius R (orthogonal to axis **11**) rotated about axis **11**.

To clarify the spatial terminology, objects **12**, **13**, and **14** are used. An axial surface, such as surface **15** of object **12**, is formed by a plane co-planar with axis **11**. Axis **11** passes through planar surface **15**; however any planar surface co-planar with axis **11** is an axial surface. A radial surface, such as surface **16** of object **13**, is formed by a plane orthogonal to axis **11** and co-planar with a radius, for example, radius **17**. Radius **17** passes through planar surface **16**; however any planar surface co-planar with radius **17** is a radial surface. Surface **18** of object **14** forms a circumferential, or cylindrical, surface. For example, circumference **19** is passes through surface **18**. As a further example, axial movement is parallel to axis **11**, radial movement is orthogonal to axis **11**, and circumferential movement is parallel to circumference **19**. Rotational movement is with respect to axis **11**. The adverbs “axially,” “radially,” and “circumferentially” refer to orientations parallel to axis **11**, radius **17**, and circumference **19**, respectively. For example, an axially disposed surface or edge extends in direction AD, a radially disposed surface or edge extends in direction R, and a circumferentially disposed surface or edge extends in direction CD.

FIG. 2 is a schematic representation of a vehicle with drive disconnect clutch assembly **100** in differential assembly **102**.

FIG. 3 is a cross-sectional view of drive disconnect clutch assembly **100** in differential assembly **102**.

FIG. 4 is a detail of drive disconnect clutch assembly **100** in FIG. 3 in a disengaged mode. The following should be viewed in light of FIGS. 2 through 4. Vehicle V has a standard four-wheel-drive vehicle architecture, for example, M is a transverse engine powering the front wheels FW via right front axle RFA, left front axle LFA, and differential assembly **102**. Assemblies **100** and **102** are used for connecting and disconnecting a secondary drive shaft SDS, for example, a rear drive shaft, with torque from motor M. Shaft SDS provides torque to rear wheels RW via rear differential assembly DIFF and rear axles RA. Assembly **100** is integrated into differential assembly **102**. Thus, as further described below, assembly **100** provides a synchronizing function and a locking clutch to engage and disengage the output/torque of the motor with SDS.

Drive disconnect clutch assembly **100** includes: axis of rotation A; input, or input component (final drive ring gear), **108**, arranged to receive torque from the motor, for example via final drive pinion shaft **103**; output, or output gear, **104**; and clutch **110**. Output **104** transmits torque to SDS via shaft **105**. Gear **108** transmits torque to LFA and RFA via differential gear set **107**. Clutch **110** includes flexible piston plate **112**, at least one clutch plate **114**, at least one wedge plate **116**, backing plate **117**, and respective friction material **118** disposed between the at least one clutch plate and the at least one wedge plate. In an example embodiment, flexible piston plate **112** is a Belleville spring. In an example embodiment, backing plate **117** is axially fixed to component **108**.

In an example embodiment, the friction material is fixed to the at least one wedge plate, but in other embodiments (not shown), the friction material may be fixed to the at least one clutch plate or the friction material may be respective separate

4

discs free of fixed connection to the wedge and clutch plates. In the example illustrated by the figures, assembly **100** includes three plates **114** and three plates **116**; however, it should be understood that assembly **100** is not limited to a particular number of plates **114** or plates **116** or a particular ratio of plates **114** to plates **116**. To simplify the presentation, the discussion that follows is directed to “plates **114**,” “clutch plates,” “plates **116**,” and “wedge plates”; however, it should be understood that the discussion is applicable to configurations including only one clutch plate or wedge plate, or only one each clutch plate and wedge plate.

As for a typical wet clutch arrangement, clutch plates **114** are keyed to the input component such that the clutch plates are axially displaceable and rotationally connected to the input component. By “rotationally connected” we mean that two or more components are directly or indirectly connected such that respective rotations of the components are locked. That is, whenever one of the components rotates, the other of the components rotates in unison. Slots **137** and splines **139** of the input component are used to engage the clutch plates.

In a disengaged mode, as shown in FIG. 4, the flexible piston plate is positioned such that the flexible piston plate does not clamp the clutch plates and the wedge plates. Further, as described below, the wedge plates are rotationally locked with the output component. Thus, the clutch plates and the input are rotatable with respect to the wedge plates and the output component and torque is not transmitted from the input to the output.

FIG. 5 is a detail of drive disconnect clutch assembly **100** in FIG. 3 in a synchronizing mode. The following should be viewed in light of FIGS. 2 through 5. As further described infra, in a synchronizing mode, the wedge plates remain rotationally connected to the output component and the flexible piston plate is arranged to displace in axial direction AD1 to clamp the clutch plates and the wedge plates to the backing plate to enable transmission of torque between the input component and the output gear. For example, actuator element **113**, engaged with portion **112A** of piston **112**, displaces in axial direction AD1 to displace piston **112** in direction AD1.

In the discussion that follows, backing plate **117** is used as an axially fixed point of reference; however, it should be understood that if plate **117** is not axially fixed, the discussion below is applicable to another axially fixed point, such as a portion of the input component. In particular: prior to initiating the synchronizing mode (as shown in FIG. 4), portion **112A** is separated from backing plate **117** by distance DIS1; and after the synchronizing mode is implemented, portion **112A** is separated from plate **117** by distance DIS2, less than DIS1.

The engagement of the clutch plates and wedge plates enables a portion of the torque generated by the motor to be transmitted to the output gear, for example, as further described infra, to synchronize energy, or rotational speeds, of the input component and the output component, as well as other components connected to the output component, such as shaft **105** and secondary drive shaft SDS. In an example embodiment of the synchronizing mode, the wedge and clutch plates slip with respect to each other to limit the torque transmitted by clutch **110**.

Clutch **110** includes wedge plate key **122** (shown in FIGS. 4, 5, and 7). Wedge plate key **122** represents only one of a plurality of keys **126** (shown in FIGS. 6 and 8). In the disengaged and synchronizing modes, keys **126** non-rotatably connect output gear **104** with the wedge plates. As further described infra, in a locked mode, following the synchronizing mode, portions **112A** and **112B** of the flexible piston plate are arranged to displace further in direction AD1 to displace

5

wedge plate key **122** (or keys **126**) to lock rotation of the wedge plates with rotation of the input component and the output gear. For example, actuator element **113** displaces further in axial direction **AD1** to displace portion **112A** and portion **112B** in direction **AD1** to displace wedge plate key **122** in radial direction **RD1** as further described below (see FIG. 7).

To initiate the locked mode, in response to the further displacement of piston **112** in direction **AD1**, portion **112C** of plate **112** (engaged with one of clutch plates **114**) slides along the clutch plate to displace in direction **RD2**. In particular, radially outermost edge **141** of portion **112C** displaces in direction **RD2**. In an example embodiment, a nominal displacement of edge **141** in direction **AD1** is possible. That is, portion **112C** is flexible to enable portions **112A** and **112B** to further displace in direction **AD1** despite edge **141** being essentially blocked from further displacement in direction **AD1**. Thus, in the locked mode, portion **112A** is separated from backing plate **117** by distance **DIS3**, less than **DIS2**. In an example embodiment, portions **112A** and **112B** are not flexible, for example, angle **AG** between portion **112B** and line **L** parallel to axis **A** is the same in the synchronizing and locked modes.

The radial displacement of piston **112** is illustrated by distances **DIS4** and **DIS5** in FIGS. 5 and 7, respectively, between edge **141** of the piston and the input component. In the synchronizing mode of FIG. 5, edge **141** is separated from the input component by distance **DIS4**. In the locked mode of FIG. 7, edge **141** has displaced radially outward so that **DIS5** is less than **DIS4**.

Specifically, to implement the locked mode, the wedge plates are expanded in direction **RD2** and wedged between the input component and the output gear. Once the wedge plates are displaced to non-rotatably connect the input component and the output gear, the full torque generated by the motor can be transferred from the input component to the output via the wedge plates. Thus, the clutch plates are no longer needed for torque transfer.

During the disengaged mode and the displacement of the piston in the synchronizing mode, the wedge plate key is engaged with the wedge plates to rotationally lock the wedge plates and the output gear. During the locked mode, the flexible piston plate is arranged to displace the wedge plate key to enable relative rotation between the wedge plates and the output component such that the wedge plates contact the input. This contact rotationally locks the wedge plates, the input component, and the output gear, enabling torque transmission between the input component and the output gear by the wedge plates without the use of the clutch plates.

FIG. 6 is a sectional view generally along line 6-6 in FIG. 5 with assembly **100** in the synchronizing mode. The following should be viewed in light of FIGS. 2 through 6. In FIG. 6, single wedge plate **116A** is shown; however, it should be understood that the discussion is applicable to the remaining wedge plates. In an example embodiment, each wedge plate includes respective slots **124**. Keys **126** are arranged to be disposed within slots **124** during the disengaged and synchronizing modes. The keys, like the wedge plate key, are rotationally connected to the output component; therefore, the keys rotationally connect the wedge plates and the output component while disposed in the slots. In the synchronizing mode, respective outer circumferences **OC1** of the wedge plates and inner circumference **IC1** of the input are separated by radial distance **131**.

FIG. 7 is a detail of drive disconnect clutch assembly **100** in FIG. 3 in a locked mode.

6

FIG. 8 is a sectional view generally along line 8-8 in FIG. 7. The following should be viewed in light of FIGS. 2 through 8. In the locked mode, the flexible piston plate is arranged to engage the wedge plate key to displace the plurality of keys radially inward such that the plurality of keys are disengaged from the plurality of slots, and the wedge plates and the output gear are rotatable with respect to each other such that the wedge plates compressively engage the input component and the output gear to non-rotatably connect the input component and the output gear. In an example embodiment, piston element **127**, engaged with the flexible piston plate, and portion **122A** of the wedge plate key are mutually angled such that as the flexible piston plate and element **127** urge **122A** in direction **AD1**, **122A** is displaced radially inward in direction **RD1**, drawing the keys out of slots **124**. In an example embodiment, in the disengaged mode, portion **112B** of the piston is free of contact with element **127** and edge **141** is in contact with a clutch plate.

In an example embodiment, the output gear includes outer circumference **OC2** with flat surfaces **128** and the wedge plate includes inner circumference **IC2** with flat surfaces **130**. Pairs of mated surfaces **128** and **130**, for example **128A** and **130A**, are at acute angle **AA** with respect to a radius **R** passing through the surfaces. That is, the surfaces form complementary ramps with respect to circumferential directions **C1** and **C2**. In the disengaged and synchronizing modes, surfaces **128** and **130** are engaged such that distance **131** between the wedge plate and the input component is present.

In the locked mode, as further described infra, enabling the wedge plates to rotate with respect to the output component, for example, withdrawing the keys from the slots, causes the wedge plates to compressively engage the input component and the output gear (distance **131** is removed) to non-rotatably connect the input component and the output gear.

In the locked mode, the wedge plates are no longer fixed by keys **126** and the wedge plates and the output gear rotate with respect to each other due to the engagement of the wedge plates with the clutch plates. For example, if the clutch plates are rotating in direction **C1**, the wedge plates rotate in direction **C1** with respect to the output gear. Respective surfaces **128** then slide along respective surfaces **130**. That is, the frictional engagement of the wedge plates with the clutch plates urges the wedge plates in direction **C1**. Due to the ramp configuration described above, as surfaces **128** slide along surfaces **130**, surfaces **128** are pushed radially outward, pushing **IC2** of the wedge plates radially outward. In turn, as further described infra, **OC1** also expands radially outward. It should be understood that movement of the clutch plates in direction **C2**, opposite **C1**, from the synchronizing position results in the same radially outward displacement of the wedge plates described above.

Thus, the wedge plates are in compressive engagement with the input component and the output gear to rotationally lock the input component and the output gear and to transmit torque between the input component and the output gear. By “compressive engagement,” we mean for example that: the input component exerts pressure radially inward on the wedge plates, which in turn exert pressure radially inward on the output gear; and/or, the output gear exerts pressure radially outward on the wedge plates, which in turn exert pressure radially outward on the input component. In an example embodiment, the rotation of the wedge plates with respect to the output component is typically small, for example, two or three degrees. However, it should be understood that other amounts of relative rotation between the wedge plates and the output component are possible.

In an example embodiment, the wedge plates are discontinuous in the circumferential directions by virtue of a radially disposed space **134** separating circumferential ends **136** of the wedge plate by circumferential distance CD. In the locked mode, the flexible piston plate, via the output gear, element **127** and wedge plate key **122**, are arranged to increase CD to expand the wedge plate radially outward. That is, space **134** enables the wedge plate to expand radially outward, in response to rotation of the wedge plates and the sliding contact of surfaces **128** and **130**, to contact the input component.

In a drive mode of the locked mode, the wedge plates remain engaged with the input component and the output gear as long as torque from the motor is present on the input component, for example in direction C1. In a coast mode, torque from the motor is withdrawn from the input component (for example, an accelerator for the motor is released) and the wheels associated with axle SA are rotating and applying torque to shaft **105**. For example, the torque from the axle causes the output gear to rotate in direction C2 with respect to the wedge plates to cause surfaces **128** and **130** to slide across each other, in a manner similar to that described above, so that the wedge plates radially expand and lock the input component with the output gear. Thus, as surfaces **128** and **130** slide toward the position associated with the synchronizing mode (keys aligned with slots **124**) the wedge plates radially contract, but as surfaces **128** and **130** slide past the position, surfaces **128** and **130** cause the wedge plates to again expand. Thus, as long as the keys remain retracted, the wedge plates continue to transmit torque in alternating drive and coast modes.

In an example embodiment, clutch **110** includes resilient element **138** engaged with keys **126** and urging keys **126** radially outward in direction RD2, for example, urging the keys into slots **124** during the disengaged and synchronizing modes. For example, when the flexible piston plate displaces in direction AD1 against the wedge plate key, the action of the flexible piston plate displaces the keys radially inward against the force of the resilient element to enable rotation of the wedge plates with respect to the output component. If the piston is retracted such that the piston no longer urges the keys radially inward, element **138** urges the keys radially outward. In the locked mode, the keys are urged against surfaces **128**, but cannot enter slots **124** due to the misalignment of the keys and slots **124**.

To disengage the clutch (disengaged mode), the piston is withdrawn (displaced in direction AD2, opposite direction AD1), and keys **126** contact surfaces **128** as described above. Then, when a transition from torque in direction C1 to torque in direction C2 occurs (or vice versa) and the wedge plates circumferentially shift, slots **124** align with keys **126** and element **138** pushes keys **126** into slots **124**, locking output component **104** and the wedge plates. The re-alignment of slots **124** and keys **126** enables OC1 to contract radially inward so that distance **131** is again formed, as described above. Therefore, the wedge plate rotates with the output gear, the wedge plate rotates independently of the input, and the clutch plates are unclamped. Thus, no torque is transmitted through assembly **100**.

Advantageously, clutch **110** synchronizes the energy of stationary components during initial clutch lock up, for example in the synchronizing mode. For example, when clutch **100** is disengaged, torque from the motor is not supplied to the “downstream” components such as the output gear, shaft **105**, and shaft SDS and these components are at rest. As described supra, to begin clutch **110** lockup, an axial force is applied by the flexible piston plate forcing frictional

engagement of the friction material with the clutch and wedge plate. The axial friction force functions in clutch **110**, for example, as for a typical automatic transmission wet clutch, until the entire driveline (including down stream components) has reached a synchronized speed, or a point near the synchronized speed such that noise, vibration, harshness (NVH) is satisfactory.

The slipping inherent in the engagement of the clutch and wedge plates for a wet clutch ensures a smooth transmission of sufficient torque to initiate rotation of the downstream components. Thus, in the synchronizing mode described supra, clamping the clutch plates and wedge plates in clutch **110** transmits torque from the motor such that the downstream components are brought from rest positions to respective rotational speeds synchronized with the input to assembly **100**.

In the locked mode described supra, when the driveline has reached the synchronized speed, or the point near the synchronized speed, clutch **110**, via the compressive engagement of the wedge plates with the input component and the output gear, transmits full driveline torque requirements to the secondary drive shaft. Thus, an abrupt transfer of torque, with an associated and undesirable jolt, is avoided by first synchronizing the driveline and then engaging the wedge plates. In addition, assembly **100** does not increase the size of a state-of-the-art bevel gear differential assembly with a disconnect clutch in the location of clutch **110**.

Although a particular configuration of clutch plates and wedge plates is shown, it should be understood that assembly **100** is not limited to the configuration shown. Other numbers of clutch plates or wedge plates are possible in order to satisfy surface area requirements for torque transfer.

It will be appreciated that various of the above-disclosed and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations, or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

What I claim is:

1. A drive disconnect clutch assembly, comprising:
  - an input component arranged to receive torque from a motor;
  - an output gear; and,
  - a clutch including:
    - a flexible piston plate;
    - at least one clutch plate;
    - at least one wedge plate; and,
    - respective friction material disposed between the at least one clutch plate and the at least one wedge plate, wherein:
      - for a synchronizing mode, the flexible piston plate is arranged to displace in a first axial direction to engage the at least one clutch plate with the at least one wedge plate to enable transfer of torque from the input component to the output gear; and,
      - for a locked mode, a first portion of the flexible piston plate is arranged to further displace in the first axial direction to enable relative rotation between the at least one wedge plate and the output gear to:
        - expand the at least one wedge plate radially outward;
        - and,
        - non-rotatably connect the at least one wedge plate, the input component, and the output gear.

9

2. The drive disconnect clutch assembly of claim 1, wherein for the locked mode, the at least one wedge plate is in contact with the input component and the output gear.

3. The drive disconnect clutch assembly of claim 1, wherein for the locked mode, a second portion of the flexible piston plate is arranged to displace radially outward.

4. The drive disconnect clutch assembly of claim 3, wherein the second portion of the flexible piston plate includes a radially outermost edge of the flexible piston plate.

5. The drive disconnect clutch assembly of claim 1, wherein in a disengaged mode:

the at least one wedge plate is non-rotatably connected to the output gear; and,

the input component is independently rotatable with respect to the output gear.

6. The drive disconnect clutch assembly of claim 1, wherein in the synchronizing mode, an outer circumference of the at least one wedge plate is free of contact with the input component.

7. The drive disconnect clutch assembly of claim 1, wherein:

the clutch includes a wedge plate key;

the wedge plate key is non-rotatably connected to the output gear;

in the synchronizing mode, the wedge plate key is engaged with the at least one wedge plate to non-rotatably connect the at least one wedge plate and the output gear; and, to initiate the locked mode, the flexible piston plate is arranged to displace the wedge plate key such that the at least one wedge plate and the output gear are rotatable with respect to each other to compressively engage the at least one wedge plate with the input component and the output gear.

8. The drive disconnect clutch assembly of claim 7, wherein:

the at least one wedge plate includes respective pluralities of slots;

the wedge plate key includes a plurality of keys arranged to be disposed within the respective pluralities of slots in the synchronizing mode; and,

the first portion of the flexible piston plate is arranged to further displace in the first axial direction to engage the wedge plate key to displace the plurality of keys radially inward such that:

the plurality of keys are disengaged from the respective pluralities of slots; and,

the at least one wedge plate and the output gear are rotatable with respect to each other to compressively engage the input component to non-rotatably connect the input component and the output gear.

9. The drive disconnect clutch assembly of claim 1, wherein:

the output gear includes an outer circumference with a first plurality of flat surfaces;

the at least one wedge plate includes at least one inner circumference with at least one second plurality of flat surfaces in contact with the first plurality of flat surfaces; and,

the first portion of the flexible piston plate is arranged to further displace in the first axial direction such that:

the at least one wedge plate and the output gear rotate with respect to each other; and,

the first plurality of flat surfaces and the at least one second plurality of flat surfaces slide across each other to displace the at least one wedge plate radially

10

outward to compressively engage the input component and non-rotatably connect the input component and the output gear.

10. The drive disconnect clutch assembly of claim 1, wherein:

the at least one wedge plate is discontinuous in a circumferential direction by virtue of at least one radially disposed space separating at least one first and second circumferential ends of the at least one wedge plate by at least one circumferential distance; and,

the first portion of the flexible piston plate is arranged to further displace in the first axial direction to increase the at least one circumferential distance to expand the at least one wedge plate radially outward.

11. The drive disconnect clutch assembly of claim 10, wherein the at least one wedge plate is arranged to expand radially outward to compressively engage the input component and the output gear to non-rotatably connect the input component and the output gear.

12. A drive disconnect clutch, comprising:

an input component arranged for driving connection to a motor;

an output gear; and,

a clutch including:

a flexible piston plate;

at least one clutch plate;

at least one wedge plate; and,

respective friction material disposed between the at least one clutch plate and the at least one wedge plate, wherein:

for a synchronizing mode, the flexible piston plate is arranged to displace a distance in a first axial direction to engage the at least one clutch plate with the at least one wedge plate to enable transfer of torque from the input component to the output gear; and,

for a locked mode a first portion of the flexible piston plate is arranged to further displace in the first axial direction to displace:

the at least one wedge plate to non-rotatably connect the input component and the output gear via contact of the at least one wedge plate with the input component and the output gear; and,

a second portion of the flexible piston plate radially outward.

13. The drive disconnect clutch assembly of claim 12, wherein the first portion of the flexible piston plate is arranged to further displace in the first axial direction to:

enable relative rotation between the at least one wedge plate and the output gear; and,

expand the at least one wedge plate radially outward.

14. The drive disconnect clutch assembly of claim 12, wherein in a disengaged mode:

the at least one wedge plate is non-rotatably connected to the output gear; and,

the input component is independently rotatable with respect to the output gear.

15. The drive disconnect clutch assembly of claim 12, wherein in the synchronizing mode, an outer circumference of the at least one wedge plate is free of contact with the input component.

16. The drive disconnect clutch assembly of claim 12, wherein:

the clutch includes a wedge plate key with a plurality of radially displaceable keys,

the wedge plate key is non-rotatably connected to the output gear;

## 11

in the synchronizing mode, the plurality of keys engages the at least one wedge plate to non-rotatably connect the at least one wedge plate and the output gear; and, in the locked mode, the flexible piston plate is arranged to displace the plurality of keys radially inward to enable relative rotation between the at least one wedge plate and the output gear.

17. The drive disconnect clutch assembly of claim 12, wherein:

the output gear includes an outer circumference with a first plurality of flat surfaces;

the at least one wedge plate includes at least one inner circumference with at least one second plurality of flat surfaces in contact with the first plurality of flat surfaces; and,

the first portion of the flexible piston plate is arranged to further displace in the first axial direction such that:

the at least one wedge plate and the output gear rotate with respect to each other; and,

the first plurality of flat surfaces and the at least one second plurality of flat surfaces slide across each other to displace the at least one wedge plate radially outward to compressively engage the input component and non-rotatably connect the input component and the output gear.

18. The drive disconnect clutch assembly of claim 12, wherein:

in a drive mode for the locked mode, the input component is arranged to rotate in a first rotational direction; and,

in a coast mode for the locked mode, the output gear is arranged to transmit torque to the at least one wedge plate such that the input component rotates in a second rotational direction, opposite the first rotational direction.

19. A drive disconnect clutch assembly, comprising:

an input component arranged to receive torque from a motor;

an output gear; and,

a clutch including:

a piston plate;

## 12

at least one clutch plate;

at least one wedge plate;

respective friction material disposed between the at least one clutch plate and the at least one wedge plate; and, a wedge plate key non-rotatably connected to the output gear and including a plurality of radially displaceable keys, wherein:

for a synchronizing mode:

the plurality of radially displaceable keys is non-rotatably connected to the at least one wedge plate; and,

the flexible piston plate is arranged to displace a distance in an axial direction to engage the at least one clutch plate with the at least one wedge plate to enable transfer of torque from the input component to the output gear; and,

for a locked mode a first portion of the flexible piston plate is arranged to further displace in the axial direction to retract the plurality of radially displaceable keys to:

enable rotation between the at least one wedge plate and the output gear;

non-rotatably connect the at least one wedge plate, the input component, and the output gear; and,

displace a second portion of the flexible piston plate radially outward.

20. The drive disconnect clutch assembly of claim 19, wherein:

the output gear includes an outer circumference formed by a first plurality of flat sides;

the at least one wedge plate includes at least one inner circumference formed by at least one second plurality of flat sides in contact with the first plurality of flat sides; and,

the first portion of the flexible piston plate is arranged to further displace in the axial direction to:

enable the first plurality of flat sides and the at least one second plurality of flat sides to slide across each other; and,

expand the at least one wedge plate radially outward.

\* \* \* \* \*