



US009777786B2

(12) **United States Patent**
Juan Lien Chang

(10) **Patent No.:** **US 9,777,786 B2**
(45) **Date of Patent:** **Oct. 3, 2017**

(54) **CLUTCH DISC WITH FASTENERS
ARRANGED AT OFFSET PITCH CIRCLES**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Schaeffler Technologies AG & Co.**
KG, Herzogenaurach (DE)
(72) Inventor: **Raymundo Juan Lien Chang, Puebla**
(MX)
(73) Assignee: **Schaeffler Technologies AG & Co.**
KG, Herzogenaurach (DE)

| | | | | | |
|-----------|-----|---------|----------|-------|------------|
| 1,855,533 | A * | 4/1932 | Tower | | F16D 13/68 |
| | | | | | 192/107 R |
| 2,100,362 | A * | 11/1937 | Stahle | | F16D 13/68 |
| | | | | | 192/207 |
| 2,296,957 | A * | 9/1942 | Spase | | F16D 13/68 |
| | | | | | 192/30 V |
| 4,260,048 | A * | 4/1981 | Beccaris | | F16D 13/64 |
| | | | | | 192/107 C |
| 4,529,078 | A * | 7/1985 | Keck | | F16D 13/64 |
| | | | | | 192/103 A |
| 4,941,558 | A * | 7/1990 | Schraut | | F16D 13/64 |
| | | | | | 192/107 C |

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 170 days.

* cited by examiner

Primary Examiner — Jacob S Scott

(21) Appl. No.: **14/740,903**

(74) *Attorney, Agent, or Firm* — Simpson & Simpson, PLLC

(22) Filed: **Jun. 16, 2015**

(65) **Prior Publication Data**
US 2016/0369850 A1 Dec. 22, 2016

(57) **ABSTRACT**


(51) **Int. Cl.**
F16D 69/04 (2006.01)
F16D 13/64 (2006.01)

A clutch disc including a drive plate concentrically arranged about an axis of rotation, the drive plate having: a first side facing a first axial direction; a second side facing a second axial direction, opposite the first axial direction. The drive plate includes a first plurality of through-bores at a first radial distance from the axis of rotation and a second plurality of through-bores at a second radial distance from the axis of rotation, where the second radial distance is different from the first radial distance. The first and second pluralities of through-bores are arranged such that an arc passes through the first and second pluralities of through-bores.

(52) **U.S. Cl.**
CPC **F16D 69/0408** (2013.01); **F16D 13/64** (2013.01); **F16D 2069/0433** (2013.01)

(58) **Field of Classification Search**
CPC F16D 13/68
See application file for complete search history.

20 Claims, 13 Drawing Sheets






Fig. 1




Fig. 2A




Fig. 2B




Fig. 3




Fig. 4




Fig. 5




Fig. 7




Fig. 8




Fig. 9




Fig. 10





Fig. 11



PRIOR ART

Fig. 12

1

CLUTCH DISC WITH FASTENERS ARRANGED AT OFFSET PITCH CIRCLES

TECHNICAL FIELD

The present disclosure relates generally to a clutch disc, and, more particularly, to a clutch plate, for a clutch disc, having a first side suitable for a first friction lining and a second side suitable for a second friction lining arranged such that an improper assembly of the friction linings on their respective sides is prevented.

BACKGROUND

FIG. 12 is an enlarged view of a portion of a prior art clutch disc with fasteners arranged at two different radial distances. The clutch disc is a critical component in a clutch that provides smooth engagement and dampens engine vibrations. Typically, the clutch disc is mounted to the input shaft between the flywheel and the clutch. Vehicles with high engine-performance-demand require clutch discs that have a friction material facing the transmission and a friction material facing the engine. Some clutch discs have the same friction material on both sides. Other clutch discs have different materials, for example, an organic friction material on the transmission side and a cerametallic friction material on the engine side. Organic material wears quicker than cerametallic material but reduces clutch chatter. Cerametallic material is more robust than organic material but results in more clutch chatter. Traditionally, the friction material is secured to the clutch disc using rivets placed circumferentially along at least one pitch circle. FIG. 12 shows typical clutch disc 80 including damper 81 and friction lining 82. Friction lining 82 is secured to clutch disc 80 with fasteners 83 and 84. Fasteners 83 are arranged along pitch circle 85 and fasteners 84 are arranged along pitch circle 86. In circumferential direction CD, fasteners 83 are not aligned with plurality of fasteners 84.

In order to facilitate assembly, the fasteners used to secure the friction materials are applied symmetrically. Unfortunately, due to the symmetrical nature of the holes in the clutch disc for receiving fasteners 83 and 84, the friction materials can be inadvertently placed on the wrong side of the clutch disc. That is, for clutch discs with a different type of friction lining on each side, the holes will accommodate either friction lining on either of the sides of the clutch disc. In that case, the clutch disc is vulnerable to excessive wear and sub-optimal performance during operation of the vehicle.

SUMMARY

According to aspects illustrated herein, there is provided a clutch disc including a drive plate concentrically arranged about an axis of rotation, the drive plate having: a first side facing a first axial direction and a second side facing a second axial direction, opposite the first axial direction. The drive plate includes a first plurality of through-bores at a first radial distance from the axis of rotation and a second plurality of through-bores at a second radial distance from the axis of rotation, where the second radial distance is different from the first radial distance. The first and second pluralities of through-bores are arranged such that an arc passes through the first and second pluralities of through-bores.

According to aspects illustrated herein, there is provided a clutch disc including a drive plate concentrically arranged

2

about an axis of rotation, the drive plate having: a first side facing a first axial direction and a second side facing a second axial direction, opposite the first axial direction. The drive plate includes a first plurality of through-bores at a first radial distance from the axis of rotation, a second plurality of through-bores at a second radial distance from the axis of rotation, where the second radial distance is different from the first radial distance, and a third plurality of through-bores at a third radial distance from the axis of rotation, different from the first and second radial distances. The first and second pluralities of through-bores are arranged such that an arc passes through the first and second pluralities of through-bores.

According to aspects illustrated herein, there is provided a drive plate concentrically arranged about an axis of rotation, the drive plate having: a first side facing a first axial direction and a second side facing a second axial direction, opposite the first axial direction. The drive plate includes a first plurality of through-bores at a first radial distance from the axis of rotation, the first plurality including a first through-bore, and a second plurality of through-bores at a second radial distance from the axis of rotation, where the second radial distance is different from the first radial distance, the second plurality including circumferentially adjacent respective second and third through-bores. The first through-bore is circumferentially disposed between the respective circumferentially adjacent second and third through-bores, the circumferentially adjacent respective second through-bore is at a first distance, in the first circumferential direction, from the first through-bore, the circumferentially adjacent respective third through-bore is at a second distance, different from the first distance, in a second circumferential direction, opposite the first circumferential direction, from the first through-bore and the first and second pluralities of through-bores are arranged such that an arc passes through the first and second pluralities of through-bores.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments are disclosed, by way of example only, with reference to the accompanying schematic drawings in which corresponding reference symbols indicate corresponding parts, in which:

FIG. 1 is a perspective view of a cylindrical coordinate system demonstrating spatial terminology used herein;

FIG. 2 is a front view of a clutch disc with fasteners arranged at two different radial distances;

FIG. 2A is a cross-sectional view taken generally along line 2A-2A in FIG. 2;

FIG. 2B is a cross-sectional view taken generally along line 2B-2B in FIG. 2;

FIG. 3 is a rear view of the clutch disc in FIG. 2;

FIG. 4 is an enlarged view of portion P4 of the clutch disc in FIG. 2;

FIG. 5 is a front perspective view of a clutch disc with fasteners arranged at three different radial distances;

FIG. 6 is a rear perspective view of a clutch disc with fasteners arranged at three different radial distances;

FIG. 7 is a front view of the clutch disc in FIG. 5;

FIG. 8 is a rear view of the clutch disc in FIG. 5;

FIG. 9 is a front view of the clutch disc in FIG. 5 with the damper removed;

FIG. 10 is a front view of the clutch disc in FIG. 5 with the damper and friction lining removed;

FIG. 11 is an enlarged view of portion P11 of the clutch disc in FIG. 7; and,

3

FIG. 12 is an enlarged view of a portion of a prior art clutch disc with fasteners arranged at two different radial distances.

DETAILED DESCRIPTION

At the outset, it should be appreciated that like drawing numbers on different drawing views identify identical, or functionally similar, structural elements of the disclosure. It is to be understood that the disclosure as claimed is not limited to the disclosed aspects.

Furthermore, it is understood that this disclosure is not limited to the particular methodology, materials and modifications described and as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to limit the scope of the present disclosure.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this disclosure belongs. It should be understood that any methods, devices or materials similar or equivalent to those described herein can be used in the practice or testing of the disclosure.

FIG. 1 is a perspective view of cylindrical coordinate system 10 demonstrating spatial terminology used in the present application. The present application is at least partially described within the context of a cylindrical coordinate system. System 10 includes longitudinal axis 11, used as the reference for the directional and spatial terms that follow. Axial direction AD is parallel to axis 11. Radial direction RD is orthogonal to axis 11. Circumferential direction CD is defined by an endpoint of radius R (orthogonal to axis 11) rotated about axis 11.

To clarify the spatial terminology, objects 12, 13, and 14 are used. An axial surface, such as surface 15 of object 12, is formed by a plane co-planar with axis 11. Axis 11 passes through planar surface 15; however any planar surface co-planar with axis 11 is an axial surface. A radial surface, such as surface 16 of object 13, is formed by a plane orthogonal to axis 11 and co-planar with a radius, for example, radius 17. Radius 17 passes through planar surface 16; however any planar surface co-planar with radius 17 is a radial surface. Surface 18 of object 14 forms a circumferential, or cylindrical, surface. For example, circumference 19 passes through surface 18. As a further example, axial movement is parallel to axis 11, radial movement is orthogonal to axis 11, and circumferential movement is parallel to circumference 19. Rotational movement is with respect to axis 11. The adverbs “axially,” “radially,” and “circumferentially” refer to orientations parallel to axis 11, radius 17, and circumference 19, respectively. For example, an axially disposed surface or edge extends in direction AD, a radially disposed surface or edge extends in direction R, and a circumferentially disposed surface or edge extends in direction CD.

FIG. 2 is a front view of clutch disc 100 with fasteners arranged at two radial distances RD1 and RD2.

FIG. 2A is a cross-sectional view taken generally along line 2A-2A in FIG. 2.

FIG. 2B is a cross-sectional view taken generally along line 2B-2B in FIG. 2.

FIG. 3 is a rear view of clutch disc 100 in FIG. 2.

FIG. 4 is an enlarged view of portion P4 of clutch disc 100 in FIG. 2. The following should be viewed in light of FIGS. 2 through 4. Clutch disc 100 includes drive plate 101 concentrically arranged about axis of rotation AR and drive

4

plate 101 includes side 104 facing axial direction AD1 and side 105 facing axial direction AD2, opposite axial direction AD1. Drive plate 101 includes through-bores 102 arranged at radial distance RD1 from axis of rotation AR and through-bores 103 arranged at radial distance RD2 from axis of rotation AR where radial distance RD1 is different from radial distance RD2. Arc A passes through through-bores 102 and 103 in circumferential direction CD. In other words, through-bores 102 and 103 are arranged such that arc A passes through through-bores 102 and 103. It should be understood that clutch disc 100 is not limited to a particular ratio of RD1 to RD2. In an example embodiment, arc A passes in circumferential direction CD.

In an example embodiment, clutch disc 100 includes damper 106 arranged radially inward of drive plate 101. When the through-bores are described as being arranged at radial distances, it is meant that the through-bores are arranged along pitch circles. The phrases “arranged at radial distances” and “arranged along pitch circles” are used interchangeably.

In an example embodiment, friction lining 108 (shown in FIG. 2) is secured to side 104 of drive plate 101 via fasteners 111 via through-bores 103. That is, fasteners 111 are disposed in through-bores 103. In other words, clutch disc 100 can include friction lining 108 secured to side 104 of drive plate 101 with fasteners 111 disposed in through-bores 103. In an example embodiment, friction lining 109 (shown in FIG. 3) is secured to side 105 of drive plate 101 via fasteners 110 via through-bores 102. That is, fasteners 110 are disposed in through-bores 102. In other words, clutch disc 100 can include friction lining 109 secured to side 105 of drive plate 101 with fasteners 110 disposed in through-bores 102. In an example embodiment, clutch disc 100 includes both friction linings 108 and 109 secured on opposing axial faces 104 and 105, respectively. It should be understood that clutch disc 100 is not limited to the particular fasteners used to secure friction linings 108 and 109 shown. For example, friction lining 108 can be secured to side 104 with any combination of fasteners 110 and 111 and friction lining 109 can be secured to side 105 with any combination of fasteners 110 and/or 111.

Referring to FIG. 2, each through-bore 102A of through-bores 102 is circumferentially disposed between pairs of through-bores 103, for example, circumferentially adjacent pairs of through-bores 103A and 103B. Through-bore 103A is arranged distance D1, in circumferential direction CD1, from through-bore 102A. Through-bore 103B is arranged distance D2, in circumferential direction CD2, from through-bore 102A. Distance D1 is smaller than distance D2; thus, through-bore 102A is asymmetrically disposed between through-bores 103A and 103B, respectively. Although through-bores 102 and 103 are shown alternating in direction CD1, it should be understood that other sequences of through-bores 102 and 103 are possible. For example, a respective through-bore 102 may not be located between each pair of circumferentially adjacent bores 103.

Since through-bores 102 are arranged radially offset from and asymmetrically between circumferentially disposed through-bores 103, friction lining 108 can be secured to side 104 only and not to side 105 by fasteners 111 and friction lining 109 can be secured to side 105 only and not to side 104 by fasteners 110. It should be understood that distances D1 and D2 can be reversed. Disc 100 is not limited to a particular ratio of distance D1 to distance D2.

In an example embodiment, friction lining 108 is a full ring of friction material, for example, organic material, secured to drive plate 101. In an example embodiment,

5

friction lining **108** is a full ring of an organic material with grooves that is fixed to individual segments via rivets and those segments are, in turn, fixed within clutch disc **100**. In an example embodiment, friction lining **109** includes portions **109P** disposed circumferentially about drive plate **101**. More specifically, friction lining **109**, in an example embodiment, includes individual cerametallic friction pads bonded to a plate and rivets fix the plate within clutch disc **100**. In the example embodiment shown in FIG. 3, friction lining **109** is circumferentially segmented and portion **109A** is a segment of circumferentially segmented friction lining **109** and circumferentially disposed between one fastener **110A** of fasteners **110** and one fastener **111A** of fasteners **111**. Fasteners **110** are arranged along a first pitch circle and fasteners **111** are arranged along a second pitch circle radially offset from the first pitch circle.

Referring to FIG. 2A, friction linings **108** and **109** are fabricated with through-bores **108A** and **109A**, respectively, arranged to be aligned with through-bores **102** to accommodate fasteners **110**. Friction linings **108** and **109** are applied to opposing axial faces **104** and **105**, respectively, and thus, are mirror images when assembled with clutch disc **100**. As mirror images, so long as friction lining **108** is applied to axial face **104** and friction lining **109** is applied to axial face **105**, through-bores **102** of drive plate **101** and through-bores **108A** and **109A** of friction linings **108** and **109**, respectively, are aligned to accommodate fasteners **110**. Similarly, referring to FIG. 2B, friction linings **108** and **109** are fabricated with through-bores **108B** and **109B**, respectively, arranged to be aligned with through-bores **103** to accommodate fasteners **111**. In other words, fasteners **110** are disposed in through-bores **108A**, **102** and **109A** and fasteners **111** are disposed in through-bores **108B**, **103** and **109B**.

Referring to FIG. 4, Fastener **110B** of fasteners **110** is circumferentially disposed between fasteners **111B** and **111C**, respectively, of fasteners **111**. Fastener **111B** is arranged distance **D1**, in circumferential direction **CD1**, from fastener **110B** and fastener **111C** is arranged distance **D2**, different from distance **D1**, in circumferential direction **CD2**, opposite circumferential direction **CD1**, from fastener **110B**. When assembled, each fastener **110** is circumferentially disposed between pairs of fasteners **111**, for example, circumferentially adjacent fasteners **111**. In an example embodiment, similarly, each through-bore **102** is circumferentially disposed between pairs of through-bores **103**, for example, circumferentially adjacent through-bores **103**.

Due to fasteners **110** and **111** being arranged asymmetrically and at different radial distances **RD1** and **RD2**, respectively, (or along offset pitch circles), if friction lining **108** is applied to axial face **105** and/or friction lining **109** is applied to axial face **104**, through-bores **102** of drive plate **101** and through-bores **108A** and **109A** of friction linings **108** and **109**, respectively, are not aligned to accommodate fasteners **110**. Similarly, through-bores **103** of drive plate **101** and through-bores **108B** and **109B** of friction linings **108** and **109**, respectively, are not aligned to accommodate fasteners **111**. This arrangement prevents the improper assembly of clutch disc **100** with friction linings **108** and **109** on faces **105** and **104**, respectively.

In an example embodiment, fasteners **110** and **111** are rivets used to bond friction linings **108** and **109** to sides **104** and **105**, respectively.

Referring to FIG. 2, in an example embodiment, friction lining **108** is made of an organic material. In an example embodiment, friction lining **108** is made of yarn (roving, aramid, copper wire, and acrylic yarn) which is coated with

6

a friction cement (rubber, resins, sulpher, glass fiber). Referring to FIG. 3, in an example embodiment, friction lining **109** is made of a cerametallic material. Cerametallic materials are more aggressive and have a higher coefficient of friction than organic materials. The combination of the organic and cerametallic materials of friction linings **108** and **109** provides increased power levels without slippage.

In an example embodiment, grooves **130** and **140** are cut into friction linings **108** and **109**, respectively, to aid cooling and release of the clutch disc.

FIG. 5 is a front perspective view of clutch disc **200** with fasteners arranged at three different radial distances.

FIG. 6 is a rear perspective view of clutch disc **200** in FIG. 5.

FIG. 7 is a front view of clutch disc **200** in FIG. 5.

FIG. 8 is a rear view of clutch disc **200** in FIG. 5.

FIG. 9 is a front view of clutch disc **200** in FIG. 5 with the damper removed.

FIG. 10 is a front view of clutch disc **200** in FIG. 5 with the damper and friction lining removed.

FIG. 11 is an enlarged view of portion **P11** of clutch disc **200** in FIG. 7. The following should be viewed in light of FIGS. 5 through 11. The previous discussion regarding the alignment of through-bores **102** and **103** with through-bores **108A**, **109A**, **108B** and **109B** of friction linings **108** and **109** to accommodate fasteners **110** and **111** is applicable to through-bores **202**, **203** and **204** and the through-bores of friction linings **209** and **210** as they accommodate fasteners **211**, **212** and **213**. In other words, the through-bores of friction linings **209** and **210** are arranged like through-bores **108A**, **109A**, **108B** and **109B** and aligned with through-bores **202**, **203** and **204** to accommodate fasteners **211**, **212** and **213**. Clutch disc **200** includes drive plate **201** concentrically arranged about axis of rotation **AR** and drive plate **201** includes side **205** facing axial direction **AD1** and side **206** facing axial direction **AD2**, opposite axial direction **AD1**. Drive plate **201** includes through-bores **202** arranged at radial distance **RD1** from axis of rotation **AR**, through-bores **203** arranged at radial distance **RD2** from axis of rotation **AR**, and through-bores **204** arranged at radial distance **RD3** from axis of rotation **AR**. Radial distances **RD1**, **RD2** and **RD3** are different. Arc **A** passes through through-bores **202** and **203**. In an example embodiment, arc **A** passes through through-bores **202** and **203** in circumferential direction **CD**. In other words, through-bores **202** and **203** are arranged such that arc **A** passes through through-bores **202** and **203**. It should be understood that clutch disc **200** is not limited to particular ratios between **RD1**, **RD2** and **RD3**. In an example embodiment, arc **A** passes in circumferential direction **CD**.

In an example embodiment, clutch disc **200** includes damper **208** arranged radially inward of drive plate **201**.

In an example embodiment, through-bores **202** are radially outward of through-bores **203** and **204**, respectively. In an example embodiment, through-bores **202** are radially inward of through-bores **203** and radially outward of through-bores **204**. In other words, through-bores **202** and **203** can be reversed.

In an example embodiment, friction lining **209** (shown in FIGS. 5, 7, 9 and 11) is secured to side **205** of drive plate **201** via fasteners **211** and **213**, respectively, via through-bores **202** and **204**, respectively. That is, fasteners **211** and **213** are disposed in through-bores **202** and **204**, respectively. In an example embodiment, friction lining **210** (shown in FIGS. 6 and 8) is secured to side **206** of drive plate **201** via fasteners **212** and **213**, respectively, via through-bores **203**, and **204**, respectively. That is, fasteners **212** and **213** are disposed in

through-bores **203**, and **204**, respectively. It should be understood that fasteners **213** secure both friction linings **209** and **210**.

In an example embodiment, clutch disc **200** includes both friction linings **209** and **210** on opposing axial faces **205** and **206**, respectively. Referring to FIG. 5, in an example embodiment, each fastener **211** is arranged a distance in circumferential direction CD2 from a circumferentially adjacent fastener **212**. Adjacent fasteners **211** and **212** in circumferential direction CD2 together with two fasteners **213** form a quadrilateral. In an example embodiment, the two radially inward fasteners **213** in the quadrilateral arrangement are arranged circumferentially between fastener **211** and circumferentially adjacent fastener **212** in circumferential direction CD2 of the quadrilateral arrangement. In an example embodiment, the quadrilateral is a trapezoid, or trapezoidal. Furthermore, it should be understood that through-bores **202**, **203** and **204** form a similar quadrilateral arrangement. For example, each through-bore **202** is arranged a distance in circumferential direction CD2 from a circumferentially adjacent through-bore **203** and the circumferentially adjacent through-bores **202** and **203** together with two radially inward through-bores **204** form a quadrilateral. In an example embodiment, the two radially inward through-bores **204** are arranged circumferentially between through-bore **202** and the circumferentially adjacent through-bore **203**. In FIG. 5, starting at 12 o'clock there are ten such quadrilateral arrangements shown. It should be understood that drive plate **201** could have additional or fewer quadrilateral arrangements. It should be understood that this quadrilateral arrangement prevents misassembly of friction linings **209** and **210** on drive plate **201**.

Referring to FIG. 10, each through-bore **202A** of through-bores **202** is circumferentially disposed between pairs of through-bores **203**, for example, circumferentially adjacent pairs of through-bores **203A** and **203B**. Through-bore **203A** is arranged distance D3, in circumferential direction CD1, from through-bore **202A**. Through-bore **203B** is arranged distance D4, in circumferential direction CD2, opposite circumferential direction CD1, from through-bore **202A**. Distance D3 is smaller than distance D4; thus, through-bore **202A** is asymmetrically disposed between through-bores **203A** and **203B**. It should be understood that distances D3 and D4 can be reversed. Clutch disc **200** is not limited to a particular ratio of distance D3 to distance D4. In an example embodiment, clutch disc **200** includes axis of rotation AR, drive plate **201** concentrically arranged about axis of rotation AR, drive plate **201** having: side **205** facing axial direction AD1 and side **206** facing axial direction AD2, opposite axial direction AD1, through-bores **202** at radial distance RD1 from axis of rotation AR, through-bores **202** including through-bore **202A** and through-bores **203** at radial distance RD2 from axis of rotation AR, through-bores **203** including through-bore **203A** and through-bore **203B**. Through-bore **202A** is circumferentially disposed between respective circumferentially adjacent through-bores **203A** and **203B**. Each through-bore **203A** is arranged at distance D3, in circumferential direction CD1, from each respective through-bore **202A**. Through-bore **203B** is arranged at distance D4, different from distance D3, in circumferential direction CD2, opposite circumferential direction CD1, from each respective through-bore **202A**. Arc A passes through through-bores **202** and **203** and through-bores **202A**, **203A** and **203B** circumferentially.

Since through-bores **202** are arranged radially offset from through-bores **203** and **204** and asymmetrically between circumferentially adjacent through-bores **203**, friction lining

209 can be secured to side **205** only and not side **206** by fasteners **211** and **213** and friction lining **210** can be secured to side **206** only and not side **205** by fasteners **212** and **213**. Although through-bores **202** and **203** are shown alternating in circumferential direction CD, it should be understood that other sequences are possible. For example, a respective through-bore **202** may not be located between each pair of circumferentially adjacent through-bores **203**.

In an example embodiment, each through-bore of through-bores **202** and each fastener of fasteners **211** are arranged, in circumferential direction CD, between two respective circumferentially adjacent through-bores **203** and fasteners **212**, respectively; and each through-bore **203** and fastener **212** are arranged, in circumferential direction CD, between two respective circumferentially adjacent through-bores **202** and fasteners **211**.

Referring to FIG. 11, fastener **211A** is circumferentially disposed between two circumferentially adjacent fasteners **212A** and **212B**. Fastener **211A** is arranged distance D5, in circumferential direction CD1, from fastener **212A** and fastener **211A** is arranged distance D6, in circumferential direction CD2, opposite circumferential direction CD1, from fastener **212B**. Distance D5 is smaller than distance D6. Thus, like through-bore **202A** being arranged asymmetrically between through-bores **203A** and **203B**, fastener **211A** is arranged asymmetrically between fasteners **212A** and **212B**.

In an example embodiment, fasteners **211** are radially outward of fasteners **212** and **213**, respectively. In an example embodiment, fasteners **211** are radially inward of fasteners **212** and radially outward of fasteners **213**. In other words, fasteners **211** and **212** can be reversed.

Due to fasteners **211**, **212** and **213** being arranged asymmetrically and at different distances RD1, RD2 and RD3, respectively, (or along offset pitch circles), if friction lining **209** is applied to side **206** and/or friction lining **210** is applied to side **205**, through-bores **202**, **203** and **204** are not aligned with the through-bores of linings **209** and **210** to accommodate fasteners **211**, **212** and **213**. This arrangement prevents the improper assembly of clutch disc **200** with friction linings **209** and **210** on faces **206** and **205**, respectively.

In an example embodiment, friction lining **209** is a full ring of friction material, for example, organic material, secured to drive plate **201**. In an example embodiment, friction lining **209** is a full ring of an organic material with grooves that is fixed to individual segments via rivets and those segments are, in turn, fixed within clutch disc **200**. In an example embodiment, friction lining **210** includes portions **214** and **215**, respectively, disposed circumferentially about drive plate **201**. In other words, friction lining **210** is circumferentially segmented. In an example embodiment, friction lining **210** includes individual cerametallic friction pads bonded to a plate and rivets fix the plate within clutch disc **200**. In the example embodiment shown in FIGS. 6 and 8, friction lining **210** is circumferentially segmented and portion **215A** is a segment of circumferentially segmented friction lining **210** and circumferentially disposed between fasteners **211B** and **213B** in circumferential direction CD1 and fasteners **212C** and **213A** in circumferential direction CD2 opposite circumferential direction CD1. In other words, portion **215A** is circumferentially disposed between four fasteners. Fasteners **211B**, **212C** and **213A** and **213B** form the quadrilateral discussed above in the description regarding FIG. 5.

In an example embodiment, friction lining **209** is made of an organic material. In an example embodiment, friction

9

lining 209 is made of yarn (roving, aramid, copper wire, and acrylic yarn) which is coated with a friction cement (rubber, resins, sulphur, glass fiber). In an example embodiment, friction lining 210 is made of a cerametallic material. Cerametallic materials are more aggressive and have a higher coefficient of friction than organic materials. The combination of the organic and cerametallic materials of friction linings 209 and 210 provides increased power levels without slippage.

In an example embodiment, clutch disc 200 includes axis of rotation AR, drive plate 201, friction lining 209, friction lining 210, and fasteners 211, 212 and 213. Drive plate 201 is concentrically arranged about axis of rotation AR and includes side 205 facing axial direction AD1 and side 206 facing axial direction AD2, opposite axial direction AD1. Fasteners 211, 212 and 213 secure friction linings 209 and 210 to sides 205 and 206, respectively, asymmetrically, such that: friction lining 209 can be secured to side 205 only and not to side 206 and friction lining 206 can be secured to side 206 only and not to side 205.

In an example embodiment, clutch disc 200 includes friction linings 209 and 210 and fasteners 211 and 212 securing friction lining 209 to side 205 and friction lining 210 to side 206, respectively. Fasteners 211 and 212 are disposed in through-bores 202 and 203, respectively. In an example embodiment, clutch disc 200 includes through-bores 204 and fasteners 213 arranged at radial distance RD3 from axis of rotation AR, different from radial distances RD1 and RD2. In this case, fasteners 211, 212 and 213 secure friction linings 209 and 210 to sides 205 and 206, respectively, via through-bores 202, 203 and 204, respectively.

Fasteners 211 are arranged at radial distance RD1 from axis of rotation AR. Fasteners 212 are arranged at radial distance RD2 from axis of rotation AR. Fasteners 213 are arranged at radial distance RD3 from axis of rotation AR. The minimum number of radial distances needed is two as shown in FIGS. 2 to 4. The number of radial distances needed for through-bores and fasteners increases depending on the size of the overall clutch disc desired.

It will be appreciated that various of the above-disclosed and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations, or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

What is claimed is:

1. A clutch disc, comprising:

a drive plate concentrically arranged about an axis of rotation, the drive plate having:

a first side facing a first axial direction; and,

a second side facing a second axial direction, opposite the first axial direction;

wherein the drive plate comprises a first plurality of through-bores at a first radial distance from the axis of rotation and a second plurality of through-bores at a second radial distance from the axis of rotation, where the second radial distance is different from the first radial distance, and wherein the first and second pluralities of through-bores are arranged such that an arc passes through the first and second pluralities of through-bores.

2. The clutch disc recited in claim 1, further comprising: a first friction lining; and,

10

a first plurality of fasteners disposed in the first plurality of through-bores and arranged to secure the first friction lining to the first side of the drive plate.

3. The clutch disc recited in claim 2, further comprising: a second friction lining; and,

a second plurality of fasteners disposed in the second plurality of through-bores and arranged to secure the second friction lining to the second side of the drive plate.

4. The clutch disc recited in claim 3, wherein the first or second friction lining is circumferentially segmented and a segment of the circumferentially segmented friction lining is circumferentially disposed between one fastener of the first plurality of fasteners and one fastener of the second plurality of fasteners.

5. The clutch disc recited in claim 1, wherein:

each first through-bore included in the first plurality of through-bores is circumferentially disposed between respective adjacent second and third through-bores included in the second plurality of through-bores;

the respective second through-bore is at a first distance, in the first circumferential direction, from the each respective first through-bore; and,

the respective third through-bore is at a second distance, different from the first distance, in a second circumferential direction, opposite the first circumferential direction, from the each respective first through-bore.

6. The clutch disc recited in claim 1, wherein each through-bore of the first plurality of through-bores is arranged, in the first circumferential direction, between two respective adjacent through-bores of the second plurality of through-bores.

7. A clutch disc, comprising:

a drive plate concentrically arranged about an axis of rotation, the drive plate having:

a first side facing a first axial direction; and,

a second side facing a second axial direction, opposite the first axial direction,

wherein the drive plate comprises a first plurality of through-bores at a first radial distance from the axis of rotation, a second plurality of through-bores at a second radial distance from the axis of rotation, where the second radial distance is different from the first radial distance, and a third plurality of through-bores at a third radial distance from the axis of rotation, different from the first and second radial distances, and wherein the first and second pluralities of through-bores are arranged such that an arc passes through the first and second pluralities of through-bores;

a first friction lining;

a first and second pluralities of fasteners disposed in the first and third pluralities of through bores, respectively, and arranged to secure the first friction lining to the first side;

a second friction lining; and,

a third plurality of fasteners disposed in the second and third pluralities of through-bores, respectively, and arranged to secure the second friction lining to the second side.

8. The clutch disc recited in claim 7, wherein the first and second pluralities of through-bores are radially outward of the third plurality of through-bores.

9. The clutch disc recited in claim 7, wherein:

each first through-bore included in the first plurality of through-bores is circumferentially disposed between respective adjacent second and third through-bores included in the second plurality of through-bores;

11

the respective second through-bore is at a first distance, in the first circumferential direction, from the each respective first through-bore; and,

the respective third through-bore is at a second distance, different from the first distance, in a second circumferential direction, opposite the first circumferential direction, from the each respective first through-bore.

10. The clutch disc recited in claim 7, wherein each through-bore of the first plurality of through-bores is arranged, in the first circumferential direction, between two respective adjacent through-bores of the second plurality of through-bores.

11. The clutch disc recited in claim 7, wherein a first through-bore of the first plurality of through-bores, a second through-bore of the second plurality of through-bores, and third and fourth adjacent through-bores of the third plurality of through-bores are arranged such that they form a quadrilateral and the third and fourth adjacent through-bores are arranged circumferentially between the first and second through-bores.

12. The clutch disc recited in claim 11, wherein the quadrilateral is a trapezoid.

13. The clutch disc recited in claim 7, wherein the first or the second friction lining is circumferentially segmented and a segment of the circumferentially segmented friction lining is disposed around one fastener of the first plurality of fasteners and one fastener of the third plurality of fasteners.

14. A clutch disc, comprising:

a drive plate concentrically arranged about an axis of rotation, the drive plate having:

- a first side facing a first axial direction;
- a second side facing a second axial direction, opposite the first axial direction;

wherein the drive plate comprises a first plurality of through-bores at a first radial distance from the axis of rotation, the first plurality including a first through-bore and a second plurality of through-bores at a second radial distance from the axis of rotation, where the second radial distance is different from the first radial distance, the second plurality including circumferentially adjacent respective second and third through-bores, and wherein:

the first through-bore is circumferentially disposed between the respective circumferentially adjacent second and third through-bores;

the circumferentially adjacent respective second through-bore is at a first distance, in the first circumferential direction, from the first through-bore;

the circumferentially adjacent respective third through-bore is at a second distance, different from the first distance, in a second circumferential direction, opposite the first circumferential direction, from the first through-bore; and,

12

the first and second pluralities of through-bores are arranged such that an arc passes through the first and second pluralities of through-bores.

15. The clutch disc recited in claim 14, further comprising:

- a first friction lining;
- a second friction lining;
- a first plurality of fasteners disposed in the first plurality of through-bores and arranged to secure the first friction lining to the first side; and,
- a second plurality of fasteners disposed in the second plurality of through-bores and arranged to secure the second friction lining to the second side.

16. The clutch disc recited in claim 14, wherein the drive plate further comprises:

- a third plurality of through-bores at a third radial distance, different from the first and second radial distances, from the axis of rotation.

17. The clutch disc recited in claim 16, further comprising:

- a first friction lining;
- a second friction lining;
- a first plurality of fasteners disposed in the first plurality of through-bores and arranged to secure the first friction lining to the first side;
- a second plurality of fasteners disposed in the second plurality of through-bores and arranged to secure the second friction lining to the second side; and,
- a third plurality of fasteners disposed in the third plurality of through-bores and arranged to secure the first friction lining to the first side and the second friction lining to the second side.

18. The clutch disc recited in claim 17, wherein the first or second friction lining is circumferentially segmented and a segment of the circumferentially segmented lining is disposed around a fastener of the first or second pluralities of fasteners and a fastener of the third plurality of fasteners.

19. The clutch disc recited in claim 17, wherein:

- the first or second friction lining is circumferentially segmented; and,
- a segment of the circumferentially segmented friction lining is circumferentially disposed between:
 - in the first circumferential direction, a fastener from the first plurality of fasteners and a first fastener from the third plurality of fasteners; and,
 - in the second circumferential direction opposite the first circumferential direction, a fastener from the second plurality of fasteners and a second fastener from the third plurality of fasteners.

20. The clutch disc recited in claim 14, wherein the first radial distance is greater than the second radial distance.

* * * * *